



Pakknippel IP68 EMC PG

- För skärmad kabel
- Integrerad dragavlastning
- Lamellinsatsens konstruktion motverkar att kabeln vrids vid åtdragning

Spesifikasjon

MATERIALE	Forniklet messing (CuZn39Pb3)
LAMELLINSATS	Polyamid PA6 V-2
PAKNING	Polykloropren-Nitrilgummi CR/NBR
O-RING	Nitrilgummi NBR
BESKYTTELSESGRAD	IP68 - 5 bar
TEMPERATUROMRÅDE	-20°C...+100°C (dynamisk) -40°C (static, short term)
FARGE	Forniklet Messing
HALOGENFRI	Ja

Varianter

EL-NUMMER	YTTERGJENGE	FOR KABEL Ø MM	L MM	DI MM	H MM	SWI MM	E1 MM	ANTALL/PKN
1242477	PG7/12,5	3 - 6,5	5	6,5	24	14	15,5	100
1242478	PG9/15,2	4 - 8	6	8	29	17	19	100
1242479	PG11/18,6	5 - 10	6	10	29,5	20	22	50
1242480	PG13,5/20,4	6 - 12	6,5	12	31,5	22	24	50
1242481	PG16/22,5	10 - 14	6,5	14	31,5	24	26,7	50
1242482	PG21/28,3	13 - 18	7	18	34	30	33,5	50
1242483	PG29/37,0	18 - 25	8	25	39	40	44	25
1242484	PG36/47,0	24 - 32	9	32	45	50	54	10
1242485	PG42/54,0	30 - 38	10	38	49	57	61	5
1242486	PG48/59,3	34 - 44	10	44	52	64	69	5