

**Busbar adapter, 45 mm, 25 A, DIN rail: 1, MSC-D...-PI, 16 A, Push in terminals**



**Part no.** BBA0-25-PI  
**Catalog No.** 199467  
**Alternate Catalog No.** BBA0-25-PI

### Delivery program

Accessories			Busbar adapters
			Approved to UL 508 For fitting to flat Cu-busbars with 60 mm between busbar centres, suitable for 5 mm and 10 mm busbar thickness
Connection technique			Push in terminals
For use with			Busbar adapter PKZ0, PKE
Rated operational voltage	$U_e$	V	690
Rated operational current	$I_e$	A	25
Terminal capacity			AWG 12 (4 mm <sup>2</sup> )
Adapter width		mm	45
Adapter length		mm	200
DIN rail		Quantity	1
Adapter width		mm	45
For use with			PKZM0...-PI, PKE...-PI + DILM7...-PI PKZM0...-PI, PKE...-PI + DILM9...-PI PKZM0...-PI, PKE...-PI + DILM12...-PI PKZM0...-PI, PKE...-PI + DILM15...-PI

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

### Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecI@ss10.0.1-27-37-03-04 [ACN951011])			
Mounting rail armament			1 mounting rail
Type of electric connection			3 conductors AWG 12
Rated current $I_n$		A	25
Min. busbar thickness		mm	5
Max. busbar thickness		mm	10
Width of the adapter		mm	45
Rail width		mm	35
Busbar distance		mm	60