

## Adapter, 25 A, Pole 3, For use with MSC-R...-PI, 16 A

**Part no.** MSFAR-25-PI  
**Catalog No.** 199473  
**Alternate Catalog No.** MSFAR-25-PI

## Delivery program

Product range			Accessories
Accessories			Busbar adapters
			Approved to UL 508
Rated operational voltage	U <sub>e</sub>	V	690
Rated operational current	I <sub>e</sub>	A	25
Terminal capacity			AWG 12 (4 mm <sup>2</sup> )
Adapter width		mm	90
Adapter length		mm	160
DIN rail		Quantity	1
For use with			MSC-R...-PI, 16 A
Pole			3

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecI@ss10.0.1-27-37-03-04 [ACN951011])			
Mounting rail armament			1 mounting rail
Type of electric connection			3 conductors AWG 12
Rated current I <sub>n</sub>		A	25
Min. busbar thickness		mm	2
Max. busbar thickness		mm	2
Width of the adapter		mm	90
Rail width		mm	24
Busbar distance		mm	60