

Busbar adapter, 90 mm, 25 A, DIN rail: 1, MSC-R...-PI, 16 A, Push in terminals

Part no. BBA0R-25-PI
Catalog No. 199468
Alternate Catalog No. BBA0R-25-PI

Delivery program

Accessories			Busbar adapters
			Approved to UL 508 For fitting to flat Cu-busbars with 60 mm between busbar centres, suitable for 5 mm and 10 mm busbar thickness
Connection technique			Push in terminals
For use with			Busbar adapter PKZ0, PKE
Rated operational voltage	U _e	V	690
Rated operational current	I _e	A	25
Terminal capacity			AWG 12 (4 mm ²)
Adapter width		mm	90
Adapter length		mm	200
DIN rail		Quantity	1
Adapter width		mm	90
For use with			PKZM0...-PI, PKE...-PI + 2 x DILM7-01...-PI PKZM0...-PI, PKE...-PI + 2 x DILM9-01...-PI PKZM0...-PI, PKE...-PI + 2 x DILM12-01...-PI

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss10.0.1-27-37-03-04 [ACN951011])			
Mounting rail armament			1 mounting rail
Type of electric connection			3 conductors AWG 12
Rated current In	A	25	
Min. busbar thickness	mm	5	
Max. busbar thickness	mm	10	
Width of the adapter	mm	90	
Rail width	mm	35	
Busbar distance	mm	60	