

# FDV-DOKUMENTASJON

Produkt:

PAKKNIPPEL POLY m/KONT.MUT. M50

|                      |               |
|----------------------|---------------|
| Elnummer:            | 1204698       |
| EAN/GTIN:            | 7070530394767 |
| Produsentens varenr: | 4410012       |
| Merkevare:           | Sonepar       |



|                                          |                |
|------------------------------------------|----------------|
| Thread type                              | Metric         |
| Nominal thread size metric/PG            | 50             |
| Nominal thread size inch/gas pipe thread | Other          |
| Pitch thread                             | 1.5 mm         |
| Thread length                            | 18 mm          |
| Wrench width                             | 60 mm          |
| Hexagon angular dimension                | 66,7 mm        |
| Suitable for cable diameter              | 30...38 mm     |
| Material                                 | Plastic        |
| Material quality                         | Polyamide (PA) |
| Surface protection                       | Untreated      |
| Halogen free                             | Yes            |
| Glass-fibre reinforced                   | No             |
| Degree of protection (IP)                | IP68           |
| Shock resistant                          | Yes            |
| Colour                                   | Grey           |
| RAL-number                               | 7035           |
| Bend radius protection/trumpet flare     | No             |
| With locknut                             | Yes            |
| Snapping in opening                      | No             |
| Model                                    | Straight       |
| Multi seal area                          | No             |
| Flat cable coupling                      | No             |
| With strain relief                       | Yes            |
| Type of sealing                          | Sealing ring   |
| Separable screw gland                    | No             |
| Operating temperature                    | -40...100 °C   |
| Explosion-tested version                 | No             |
| For Ex-zone gas                          | None           |
| For Ex-Zone dust                         | None           |
| For armoured cable                       | No             |
| EMC-version                              | No             |
| Screened                                 | No             |



PRODUSENT / LEVERANDØR  
**Sonepar Norge AS**  
Nedre Eikervei 65  
3001 Drammen

TLF:  
+47 82 86 10 50  
WEB:  
Sonepar.no