

# Eaton 102681

Catalog Number: 102681

Eaton Moeller series NZM - Molded Case Circuit Breaker. Molded Case Switch, 3p, 63A

Photo is representative

## General specifications



**Product Name** Catalog Number

Eaton Moeller series NZM molded case switch 102681

**Model Code**

NS1-63-NA

**EAN** Product Length/Depth

4015081025411 88 mm

**Product Height** Product Width

145 mm 90 mm

**Product Weight** Compliances

1.046 kg RoHS conform

## Certifications

IEC

CE marking

UL listed

UL/CSA

UL (Category Control Number WJAZ)

CSA (File No. 22086)

UL (File No. E148671)

IEC 60947-2

UL 489

CSA-C22.2 No. 5-09

CSA (Class No. 4652-06)

CSA certified

Specially designed for North America

## defaultTaxonomyAttributeLabel

### Type

Switch-disconnector

### Special features

IEC/EN 60947-2: circuit breakers without overcurrent (CBI-X) with main switch characteristics and isolating characteristics to IEC/EN 60204.  
Rated current = rated uninterrupted current: 63 A  
Terminal capacity hint: Up to 95 mm<sup>2</sup> can be connected depending on the cable manufacturer.

### Application

Branch circuits, feeder circuits

### Amperage Rating

63 A

### Voltage rating

690 V - 690 V

### Circuit breaker frame type

N1

### Features

Protection unit

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

### Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Certification reports

[DA-DC-03\\_NS1](#)

### Characteristic curve

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-002.eps](#)

[eaton-circuit-breaker-nzm-mccb-characteristic-curve.eps](#)

### Drawings

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps](#)

[eaton-circuit-breaker-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-006.eps](#)

### eCAD model

[DA-CE-ETN.NS1-63-NA](#)

### Installation instructions

[eaton-circuit-breaker-switch-disconnector-nzmb-il01203004z.pdf](#)

### Installation videos

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

### mCAD model

[DA-CS-nzml\\_xsve](#)

[DA-CD-nzml\\_xsve](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

## 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

## 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

## 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

## 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

## 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## 10.4 Clearances and creepage distances

Meets the product standard's requirements.

## 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

## 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

## 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

## 10.8 Connections for external conductors

Is the panel builder's responsibility.

## 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

## 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Pollution degree

3

#### Mounting Method

Fixed

DIN rail (top hat rail) mounting optional

Built-in device fixed built-in technique

#### Equipment heat dissipation, current-dependent

6.69 W

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

70 °C

#### Ambient storage temperature - min

40 °C

#### Rated current (I<sub>u</sub>)

125 A

#### Current rating (I<sub>u</sub>) (UL 489 csa 22.2 no. 5.1)

125 A

#### Number of auxiliary contacts (change-over contacts)

0

#### Number of auxiliary contacts (normally closed contacts)

0

#### Number of auxiliary contacts (normally open contacts)

0

#### Switch positions

I, +, 0

#### Degree of protection

IP20

In the area of the HMI devices: IP20 (basic protection type)

#### Direction of incoming supply

As required

#### Electrical connection type of main circuit

Frame clamp

**Lifespan, mechanical**

20000 operations

**Overvoltage category**

III

**Degree of protection (IP), front side**

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

**Degree of protection (terminations)**

IP00 (terminations, phase isolator and band terminal)

IP10 (tunnel terminal)

**Number of poles**

Three-pole

**Terminal capacity (copper strip)**

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Max. 9 segments of 9 mm x 0.8 mm at box terminal

**Lifespan, electrical**

10000 operations at 415 V AC-1

7500 operations at 690 V AC-1

10000 operations at 400 V AC-1

**Functions**

Disconnectors/main switches

**Position of connection for main current circuit**

Front side

**Rated operational current for specified heat dissipation (In)**

63 A

**Power loss**

6.7 W

**Short-circuit total breaktime**

< 10 ms

**Short-circuit release non-delayed setting - max**

1250 A

**Short-circuit release non-delayed setting - min**

1250 A

**Terminal capacity (copper busbar)**

Min. 12 mm x 5 mm direct at switch rear-side connection

NA: min. 12 mm x 5 mm direct at switch rear-side connection

Max. 16 mm x 5 mm direct at switch rear-side connection

M6 at rear-side screw connection

NA: max. 16 mm x 5 mm direct at switch rear-side connection

NA: M6 at rear-side screw connection

**Terminal capacity (copper solid conductor/cable)**

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal

NA: 9 - 6 AWG (2x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

NA: 12 - 6 AWG (1x) at box terminal

NA: 6 AWG (1x) at tunnel terminal

NA: 12 - 6 AWG (1x) direct at switch rear-side connection

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

**Terminal capacity (aluminum solid conductor/cable)**

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

**Terminal capacity (copper stranded conductor/cable)**

NA: 4 - 2/0 AWG/kcmil (1x) at box terminal

10 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) at box terminal

NA: 4 - 3/0 AWG/kcmil (1x) at 1-hole tunnel terminal

6 mm<sup>2</sup> - 25 mm<sup>2</sup> (2x) at box terminal

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

25 mm<sup>2</sup> (2x) direct at switch rear-side connection

25 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) direct at switch rear-side connection

**Terminal capacity (aluminum stranded conductor/cable)**

25 mm<sup>2</sup> - 35 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

25 mm<sup>2</sup> - 35 mm<sup>2</sup> (2x) direct at switch rear-side connection

**Handle type**

Rocker lever

**Short delay current setting (Isd) - max**

0 A

**Short delay current setting (Isd) - min**

0 A

**Instantaneous current setting (li) - max**

1250 A

**Instantaneous current setting (li) - min**

1250 A

**Number of operations per hour - max**

120

**Overload current setting (Ir) - max**

0 A

Overload current setting (Ir) - min

0 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz

85 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

50 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

35 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

10 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

7.5 kA

Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

105 kA

Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

74 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz

53 kA

Rated short-circuit making capacity Icm at 690 V, 50/60 Hz

17 kA

Standard terminals

Box terminal

Optional terminals

Connection on rear. Screw terminal. Tunnel terminal

Rated operating voltage Ue (UL) - max

480 Y / 277 V

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz

187 kA

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

6000 V

Rated insulation voltage (Ui)

690 V AC



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)