

# Eaton 102685

Catalog Number: 102685

Eaton Moeller series NZM - Molded Case Circuit Breaker. Molded Case Switch, 3p, 200A



Photo is representative

## General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case switch	102685
Model Code	NS2-200-NA
EAN	Product Length/Depth
4015081025459	142 mm
Product Height	Product Width
185 mm	105 mm
Product Weight	Compliances
2.423 kg	RoHS conform
Certifications	
CSA (File No. 22086)	
UL/CSA	
IEC	
CSA (Class No. 4652-06)	
UL (File No. E148671)	
UL 489	
Specially designed for North America	
UL listed	
CSA-C22.2 No. 5-09	
IEC 60947-2	
CE marking	
UL (Category Control Number WJAZ)	
CSA certified	

## defaultTaxonomyAttributeLabel

### Type

Switch-disconnector

### Special features

IEC/EN 60947-2: circuit  
breakers without overcurrent  
(CBI-X) with main switch  
characteristics and isolating  
characteristics to IEC/EN  
60204.  
Rated current = rated  
uninterrupted current: 200 A

### Application

Branch circuits, feeder circuits

### Amperage Rating

200 A

### Voltage rating

690 V - 690 V

### Circuit breaker frame type

N2

### Features

Motor drive optional

Protection unit

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

## Resources

### Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Certification reports

[DA-DC-03\\_NS2](#)

### Characteristic curve

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-005.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-037.eps](#)

### Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-019.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-3d-drawing.eps](#)

### eCAD model

[ETN.NS2-200-NA](#)

### Installation instructions

[eaton-circuit-breakers-nzm2-basic-device-bg2-instruction-leaflet-il01206006z.pdf](#)

### Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### mCAD model

[DA-CS-nzm2\\_3p](#)

[DA-CD-nzm2\\_3p](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

**Pollution degree**

3

**Mounting Method**

Built-in device fixed built-in technique

DIN rail (top hat rail) mounting optional

Fixed

**Equipment heat dissipation, current-dependent**

38.04 W

**Ambient operating temperature - max**

70 °C

**Ambient operating temperature - min**

-25 °C

**Ambient storage temperature - max**

70 °C

**Ambient storage temperature - min**

40 °C

**Rated current (I<sub>u</sub>)**

250 A

**Current rating (I<sub>u</sub>) (UL 489 csa 22.2 no. 5.1)**

250 A

**Number of auxiliary contacts (change-over contacts)**

0

**Number of auxiliary contacts (normally closed contacts)**

0

**Number of auxiliary contacts (normally open contacts)**

0

**Switch positions**

I, +, 0

**Degree of protection**

IP20

In the area of the HMI devices: IP20 (basic protection type)

**Direction of incoming supply**

As required

**Electrical connection type of main circuit**

Screw connection

**Lifespan, mechanical**

20000 operations

Overvoltage category

III

Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

Degree of protection (terminations)

IP00 (terminations, phase isolator and band terminal)

IP10 (tunnel terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

Max. 8 segments of 15.5 mm x 0.8 mm (2x) at terminal box

Max. 10 segments of 16 mm x 0.8 mm at box terminal

Max. 10 segments of 24 mm x 0.8 mm at rear-side connection  
(punched)

NA: min. 2 segments of 16 mm x 0.8 mm at rear-side connection  
(punched)

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Min. 2 segments of 16 mm x 0.8 mm at rear-side connection  
(punched)

NA: max. 10 segments of 16 mm x 0.8 mm at rear-side  
connection (punched)

Lifespan, electrical

10000 operations at 400 V AC-1

6500 operations at 400 V AC-3

10000 operations at 415 V AC-1

6500 operations at 415 V AC-3

5000 operations at 690 V AC-3

7500 operations at 690 V AC-1

Functions

Disconnectors/main switches

Position of connection for main current circuit

Front side

Rated operational current for specified heat dissipation (In)

200 A

Power loss

30.7 W

Short-circuit total breaktime

< 10 ms

Short-circuit release non-delayed setting - max

2500 A

**Short-circuit release non-delayed setting - min**

2500 A

**Terminal capacity (copper busbar)**

Max. 24 mm x 8 mm direct at switch rear-side connection  
NA: max. 20 mm x 5 mm direct at switch rear-side connection  
NA: min. 16 mm x 5 mm direct at switch rear-side connection  
M8 at rear-side screw connection  
NA: M8 at rear-side screw connection  
Min. 16 mm x 5 mm direct at switch rear-side connection

**Terminal capacity (copper solid conductor/cable)**

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal  
4 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection  
16 mm<sup>2</sup> (1x) at tunnel terminal  
NA: 12 - 6 AWG (1x) direct at switch rear-side connection  
10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection  
6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal  
NA: 12 - 6 AWG (1x) at box terminal  
NA: 6 AWG (1x) at tunnel terminal

**Terminal capacity (aluminum solid conductor/cable)**

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection  
10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection  
16 mm<sup>2</sup> (1x) at tunnel terminal

**Terminal capacity (copper stranded conductor/cable)**

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at box terminal  
25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) at box terminal  
25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) direct at switch rear-side connection  
NA: 4 - 350 AWG/kcmil (1x) at 1-hole tunnel terminal  
NA: 4 - 350 AWG/kcmil (1x) at box terminal  
25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal  
25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection

**Terminal capacity (aluminum stranded conductor/cable)**

25 mm<sup>2</sup> - 35 mm<sup>2</sup> (2x) direct at switch rear-side connection  
25 mm<sup>2</sup> - 35 mm<sup>2</sup> (1x) direct at switch rear-side connection  
25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

**Handle type**

Rocker lever

**Short delay current setting (Isd) - max**

0 A

**Short delay current setting (Isd) - min**

0 A

**Instantaneous current setting (li) - max**

2500 A

Instantaneous current setting (li) - min

2500 A

Number of operations per hour - max

120

Overload current setting (Ir) - max

0 A

Overload current setting (Ir) - min

0 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz

150 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

150 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

130 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

37.5 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

5 kA

Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

330 kA

Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

286 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz

105 kA

Rated short-circuit making capacity Icm at 690 V, 50/60 Hz

53 kA

Standard terminals

Screw terminal

Optional terminals

Box terminal. Connection on rear. Tunnel terminal

Rated operating voltage Ue (UL) - max

600 Y / 347 V

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz

330 kA

Rated impulse withstand voltage (Uiimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uiimp) at main contacts

8000 V

Rated insulation voltage (Ui)

1000 V AC



Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)