

# Eaton 265724

Catalog Number: 265724

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 160A, N2-M160



Photo is representative

## General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker thermo-magnetic	265724
Model Code	NZMN2-M160
EAN	Product Length/Depth
4015082657246	149 mm
Product Height	Product Width
184 mm	105 mm
Product Weight	Warranty
2.325 kg	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
RoHS conform	IEC/EN 60947
	IEC

## defaultTaxonomyAttributeLabel

### Type

Circuit breaker

### Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity  $I_{cn}$ )  
Rated current = rated uninterrupted current: 160 A  
Tripping class 10 A  
IEC/EN 60947-4-1, IEC/EN 60947-2  
The circuit-breaker fulfills all requirements for AC-3 switching category.

### Application

Use in unearthed supply systems at 690 V

### Amperage Rating

160 A

### Voltage rating

690 V - 690 V

### Circuit breaker frame type

NZM2

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

### Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

### Catalogs

Compact circuit-breakers and switch-disconnectors up to 1600 A

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### Certification reports

[DA-DC-03\\_N2](#)

### Characteristic curve

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-052.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-036.eps](#)

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-004.eps](#)

### Drawings

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-nzm-mccb-dimensions-019.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

### eCAD model

[ETN.265724.edz](#)

[ETN.NZMN2-M160](#)

### Installation instructions

[eaton-circuit-breakers-nzm2-basic-device-bg2-instruction-leaflet-il01206006z.pdf](#)

### Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### mCAD model

[DA-CD-nzm2\\_3p](#)

[DA-CS-nzm2\\_3p](#)

### Specifications and datasheets

[Product Data Sheet - NZMN2-M160](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

### Wiring diagrams

[eaton-manual-motor-starters-starter-nzm-mccb-wiring-diagram.eps](#)

## 10.2.2 Corrosion resistance

Meets the product standard's requirements.

eaton-manual-motor-starters-starter-msc-r-reversing-starter-wiring-diagram.eps

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## 10.4 Clearances and creepage distances

Meets the product standard's requirements.

## 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

## 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

## 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

## 10.8 Connections for external conductors

Is the panel builder's responsibility.

## 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

## 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

##### Fitted with:

Thermal protection

##### Pollution degree

3

##### Mounting Method

Fixed

Built-in device fixed built-in technique

##### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

##### Equipment heat dissipation, current-dependent

38.4 W

##### Utilization category

A (IEC/EN 60947-2)

##### Isolation

300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

##### Ambient operating temperature - max

70 °C

##### Ambient operating temperature - min

-25 °C

##### Ambient storage temperature - max

70 °C

##### Ambient storage temperature - min

40 °C

##### Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

##### Rated insulation voltage (Ui)

1000 V

##### Rated operating power at AC-3, 230 V

45 kW

##### Rated operating power at AC-3, 400 V

90 kW

##### Switch off technique

Thermomagnetic

## Connection

Screw

### Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

### Direction of incoming supply

As required

### Electrical connection type of main circuit

Screw connection

### Lifespan, mechanical

20000 operations

### Overvoltage category

III

### Rated operational current

134 A (400 V AC-3)

### Degree of protection (IP), front side

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

### Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

### Number of poles

Three-pole

### Terminal capacity (copper strip)

Max. 10 segments of 24 mm x 0.8 mm at rear-side connection  
(punched)

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Max. 8 segments of 24 mm x 1 mm (2x) at box terminal

Min. 2 segments of 16 mm x 0.8 mm at rear-side connection  
(punched)

Max. 10 segments of 16 mm x 0.8 mm at box terminal

### Lifespan, electrical

7500 operations at 690 V AC-1

10000 operations at 400 V AC-1

10000 operations at 415 V AC-1

6500 operations at 415 V AC-3

6500 operations at 400 V AC-3

5000 operations at 690 V AC-3

## Functions

Motor protection

**Shock resistance**

20 g (half-sinusoidal shock 20 ms)

**Rated operational current for specified heat dissipation (In)**

160 A

**Rated short-time withstand current (t = 0.3 s)**

1.9 kA

**Rated short-time withstand current (t = 1 s)**

1.9 kA

**Short-circuit release non-delayed setting - max**

2240 A

**Short-circuit release non-delayed setting - min**

1280 A

**Handle type**

Rocker lever

**Instantaneous current setting (Ii) - max**

2240 A

**Instantaneous current setting (Ii) - min**

1280 A

**Number of operations per hour - max**

120

**Overload current setting (Ir) - max**

160 A

**Overload current setting (Ir) - min**

125 A

**Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz**

85 kA

**Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz**

35 kA

**Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz**

35 kA

**Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz**

25 kA

**Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz**

5 kA

## Standard terminals

Screw terminal

## Optional terminals

Box terminal. Connection on rear. Tunnel terminal

## Release system

Thermomagnetic release

## Short-circuit total breaktime

< 10 ms

## Terminal capacity (aluminum solid conductor/cable)

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

## Terminal capacity (aluminum stranded conductor/cable)

25 mm<sup>2</sup> - 50 mm<sup>2</sup> (2x) direct at switch rear-side connection

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at tunnel terminal

25 mm<sup>2</sup> - 50 mm<sup>2</sup> (1x) direct at switch rear-side connection

## Terminal capacity (control cable)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)

## Terminal capacity (copper busbar)

Min. 16 mm x 5 mm direct at switch rear-side connection

M8 at rear-side screw connection

Max. 24 mm x 8 mm direct at switch rear-side connection

## Terminal capacity (copper solid conductor/cable)

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

## Terminal capacity (copper stranded conductor/cable)

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at box terminal

25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) direct at switch rear-side connection

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) at box terminal

## Rated short-circuit breaking capacity Icu (IEC/EN 60947) at 400/415 V, 50/60 Hz

35 kA

## Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

105 kA

## Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

74 kA

Rated short-circuit making capacity  $I_{cm}$  at 525 V, 50/60 Hz

53 kA

Rated short-circuit making capacity  $I_{cm}$  at 690 V, 50/60 Hz

40 kA

Rated short-circuit making capacity  $I_{cm}$  at 240 V, 50/60 Hz

187 kA

Rated impulse withstand voltage (Ui<sub>imp</sub>) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Ui<sub>imp</sub>) at main contacts

8000 V

Power loss

38.4 W



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia