

Eaton 142267

Catalog Number: 142267

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 400A 1000VDC



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Moeller series NZM switch-disconnector	142267
	Model Code
	N3-4-400-S1-DC
EAN	Product Length/Depth
4015081389971	166 mm
Product Height	Product Width
275 mm	185 mm
Product Weight	Compliances
7.3 kg	RoHS conform
Certifications	
IEC	

Type

DC switch-disconnector Switch-disconnector

Special features

IEC/EN 60947-3 CCC China Compulsory Certificate Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. N switch-disconnectors can be combined with NZM...-XU, NZM...-XA shunt releases and auxiliary contacts as well as with NZM...-XR... remote operator. For DC switching, all 4 contacts must be connected in series. Refer to the information on jumper kit accessories. Supplied as standard: Screw connection box terminal optional. When working with ungrounded systems (e.g., IT), the installation must ensure that a double ground fault will be impossible. Switch can not be combined with plug-in/withdrawable units and/or connection on rear. N4-4-...-S15-DC feeder unit and outgoer from the bottom only. Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage release Rated current = rated uninterrupted current: 400 A Values for rated uninterrupted current at 65 °C include jumpers.

Application

Open areas Utility buildings

Amperage Rating

400 A

Voltage rating

1000 V - 1000 V

Circuit breaker frame type

N3

Features

Version as main switch
Version as emergency stop installation
Motor drive optional
Remote operation with shunt releases / remote operator
Version as maintenance-/service switch

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)
[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

Certification reports

[DA-DC-03_N3](#)

Drawings

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-016.eps](#)
[eaton-circuit-breaker-nzm-mccb-dimensions-021.eps](#)
[eaton-circuit-breaker-terminals-nzm-switch-disconnector-3d-drawing-003.eps](#)
[eaton-circuit-breaker-nzm-switch-disconnector-3d-drawing.eps](#)
[eaton-circuit-breaker-nzm-switch-disconnector-3d-drawing-003.eps](#)
[eaton-circuit-breaker-terminals-nzm-switch-disconnector-3d-drawing-002.eps](#)
[eaton-circuit-breaker-nzm-switch-disconnector-3d-drawing-002.eps](#)
[eaton-circuit-breaker-cable-nzm-mccb-3d-drawing-003.eps](#)
[eaton-circuit-breaker-terminals-nzm-switch-disconnector-3d-drawing.eps](#)

eCAD model

[DA-CE-ETN.N3-4-400-S1-DC](#)

Installation instructions

[eaton-circuit-breaker-n3-4-s1-15-dc-il01208012z.pdf](#)

Installation videos

[Introduction of the new digital circuit breaker NZM](#)
[The new digital NZM Range](#)

mCAD model

[DA-CD-nzm3_4p](#)
[DA-CS-nzm3_4p](#)

Technical data sheets

[eaton-nzm-technical-information-sheet](#)

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Pollution degree

3

Mounting Method

Ground mounting

Built-in device fixed built-in technique

Distribution board installation

Fixed

Intermediate mounting

Equipment heat dissipation, current-dependent

96 W

Utilization category

DC-22 A

Rated short-time withstand current (I_{cw})

6.6 kA

Degree of protection

IP20

Electrical connection type of main circuit

Screw connection

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

40 °C

Current rating (I_u) at 40°C with terminal jumpers

400 A

Current rating (I_u) at 65°C with terminal jumpers

400 A

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Rated insulation voltage (Ui)

1250 V

Rated operating power at AC-23, 400 V

0 kW

Rated operating power at AC-3, 400 V

0 kW

Switch positions

I, +, 0

Lifespan, mechanical

15000 operations

Overvoltage category

III

Rated operational current

400 A (DC 22-A)

Degree of protection (IP), front side

IP20

Number of poles

Four-pole

Terminal capacity (copper strip)

Max. 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm at rear-side connection (punched)

Max. 8 segments of 24 mm x 1 mm (2x) at box terminal

Min. 6 segments of 16 mm x 0.8 mm at box terminal

Min. 6 segments of 16 mm x 0.8 mm at rear-side connection (punched)

10 segments of 50 mm x 1 mm (2x) at rear-side width extension

Max. 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm

Handle color

Black

Functions

Photovoltaic applications

Voltage release optional

Disconnectors/main switches

Interlockable

Number of switches

1

Rated conditional short-circuit current (I_q)

0 kA

Rated conditional short-circuit current with back-up fuse

2 x 250 AgR

15 kA at 1000 V

Rated operating voltage (U_e) at AC - max

0 V

Rated operational current for specified heat dissipation (I_n)

400 A

Rated permanent current at AC-21, 400 V

0 A

Rated permanent current at AC-23, 400 V

0 A

Rated short-time withstand current ($t = 1$ s)

6.6 kA

Switching power at 400 V

0 kW

Handle type

Rocker lever

Number of operations per hour - max

60

Standard terminals

Screw terminal

Short-circuit protective device fuses - max

2 x 250 A gR

Terminal capacity (copper busbar)

Max. 10 mm x 50 mm (2x) at rear-side width extension

M10 at rear-side screw connection

Min. 20 mm x 5 mm direct at switch rear-side connection

Max. 30 mm x 10 mm + 30 mm x 5 mm direct at switch rear-side connection

Terminal capacity (copper solid conductor/cable)

16 mm² (2x) at box terminal

16 mm² (2x) direct at switch rear-side connection

16 mm² (1x) direct at switch rear-side connection

Terminal capacity (aluminum solid conductor/cable)

16 mm² (1x) at tunnel terminal

Terminal capacity (copper stranded conductor/cable)

35 mm² - 240 mm² (1x) at box terminal

50 mm² - 240 mm² (1x) at 2-hole tunnel terminal

25 mm² - 240 mm² (2x) direct at switch rear-side connection

50 mm² - 240 mm² (2x) at 2-hole tunnel terminal

25 mm² - 185 mm² (1x) at tunnel terminal

25 mm² - 120 mm² (2x) at box terminal

25 mm² - 240 mm² (1x) direct at switch rear-side connection

Terminal capacity (aluminum stranded conductor/cable)

25 mm² - 185 mm² (1x) at tunnel terminal



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia