

# Eaton 113358

Catalog Number: 113358

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 50A, plug-in module, H2-M50-SVE



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker thermo-magnetic	113358
	Model Code
	NZMH2-M50-SVE
EAN	Product Length/Depth
4015081128938	180 mm
Product Height	Product Width
245 mm	105 mm
Product Weight	Compliances
2.785 kg	RoHS conform
Certifications	
IEC	
IEC/EN 60947	

## Type

Circuit breaker

## Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I<sub>cn</sub>)

Rated current = rated uninterrupted current: 50 A

Tripping class 10 A

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

## Application

Use in unearthed supply systems at 690 V

## Amperage Rating

50 A

## Voltage rating

690 V - 690 V

## Circuit breaker frame type

NZM2

## Accessories required

NZM2-XSVS

## 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

## 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

## 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

## 10.13 Mechanical function

## Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

## Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

## Characteristic curve

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-005.eps](#)

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-052.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-037.eps](#)

## Drawings

[eaton-circuit-breaker-adapter-nzm-mccb-dimensions-002.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-nzm-mccb-dimensions-019.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-3d-drawing.eps](#)

## Installation instructions

[eaton-circuit-breakers-nzm2-basic-device-bg2-instruction-leaflet-il01206006z.pdf](#)

IL01219023Z

## Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

## mCAD model

[DA-CD-nzm2\\_xsve](#)

[DA-CS-nzm2\\_xsve](#)

## Technical data sheets

[eaton-nzm-technical-information-sheet](#)

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Fitted with:

Thermal protection

#### Pollution degree

3

#### Mounting Method

Built-in device plug-in technique

Plug-in unit

#### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

#### Equipment heat dissipation, current-dependent

17.03 W

#### Utilization category

A (IEC/EN 60947-2)

#### Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

70 °C

#### Ambient storage temperature - min

40 °C

#### Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

#### Rated insulation voltage (Ui)

1000 V

#### Rated operating power at AC-3, 230 V

15 kW

#### Rated operating power at AC-3, 400 V

22 kW

#### Switch off technique

Thermomagnetic

#### Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

#### Direction of incoming supply

As required

#### Electrical connection type of main circuit

Screw connection

#### Lifespan, mechanical

20000 operations

#### Overvoltage category

III

#### Rated operational current

41 A (400 V AC-3)

#### Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

#### Degree of protection (terminations)

IP00 (terminations, phase isolator and strip terminal)

IP10 (tunnel terminal)

#### Number of poles

Three-pole

#### Terminal capacity (copper strip)

Max. 10 segments of 24 mm x 0.8 mm at rear-side connection  
(punched)

Min. 2 segments of 16 mm x 0.8 mm at rear-side connection  
(punched)

Max. 10 segments of 16 mm x 0.8 mm at box terminal

Min. 2 segments of 9 mm x 0.8 mm at box terminal

Max. 8 segments of 24 mm x 1 mm (2x) at box terminal

#### Lifespan, electrical

6500 operations at 400 V AC-3

5000 operations at 690 V AC-3

6500 operations at 415 V AC-3

10000 operations at 400 V AC-1

10000 operations at 415 V AC-1

7500 operations at 690 V AC-1

#### Functions

Motor protection

#### Shock resistance

20 g (half-sinusoidal shock 20 ms)

#### Rated operational current for specified heat dissipation (I<sub>n</sub>)

50 A

#### Rated short-time withstand current (t = 0.3 s)

1.9 kA

#### Rated short-time withstand current (t = 1 s)

1.9 kA

#### Short-circuit release non-delayed setting - max

700 A

#### Short-circuit release non-delayed setting - min

400 A

#### Handle type

Rocker lever

#### Instantaneous current setting (I<sub>i</sub>) - max

700 A

#### Instantaneous current setting (I<sub>i</sub>) - min

400 A

#### Number of operations per hour - max

120

#### Overload current setting (I<sub>r</sub>) - max

50 A

#### Overload current setting (I<sub>r</sub>) - min

40 A

#### Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz

150 kA

#### Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz

130 kA

#### Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz

130 kA

#### Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 525 V, 50/60 Hz

37.5 kA

#### Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 690 V, 50/60 Hz

5 kA

## Standard terminals

Screw terminal

## Optional terminals

Box terminal. Connection on rear. Tunnel terminal

## Release system

Thermomagnetic release

## Short-circuit total breaktime

< 10 ms

## Terminal capacity (aluminum solid conductor/cable)

16 mm<sup>2</sup> (1x) at tunnel terminal

## Terminal capacity (aluminum stranded conductor/cable)

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at tunnel terminal

## Terminal capacity (control cable)

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

## Terminal capacity (copper busbar)

Max. 24 mm x 8 mm direct at switch rear-side connection

Min. 16 mm x 5 mm direct at switch rear-side connection

M8 at rear-side screw connection

## Terminal capacity (copper solid conductor/cable)

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

## Terminal capacity (copper stranded conductor/cable)

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) direct at switch rear-side connection

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at box terminal

25 mm<sup>2</sup> - 70 mm<sup>2</sup> (2x) at box terminal

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

## Rated short-circuit breaking capacity I<sub>cu</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz

130 kA

## Rated short-circuit making capacity I<sub>cm</sub> at 400/415 V, 50/60 Hz

330 kA

## Rated short-circuit making capacity I<sub>cm</sub> at 440 V, 50/60 Hz

286 kA

## Rated short-circuit making capacity I<sub>cm</sub> at 525 V, 50/60 Hz

105 kA

Rated short-circuit making capacity Icm at 690 V, 50/60 Hz  
40 kA

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz  
330 kA

Rated impulse withstand voltage (Uimp) at auxiliary contacts  
6000 V

Rated impulse withstand voltage (Uimp) at main contacts  
8000 V

Power loss  
17 W



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)