

# Eaton 168526

Catalog Number: 168526

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3 p, 400A, plug-in module



## General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker electronic	168526
Model Code	NZMS3-VE400-SVE
EAN	Product Length/Depth
4015081650033	335 mm
Product Height	Product Width
215.2 mm	140 mm
Product Weight	Compliances
7.72 kg	RoHS conform

## defaultTaxonomyAttributeLabel

### Amperage Rating

400 A

### Voltage rating

690 V - 690 V

### Features

Motor drive optional

Protection unit

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

### Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

### eCAD model

[DA-CE-ETN.NZMS3-VE400-SVE](#)

### Installation instructions

[IL01219023Z](#)

### Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

### mCAD model

[nzmh3\\_me220\\_sve.stp](#)

[nzmh3\\_me220\\_sve.dwg](#)

### Technical data sheets

[eaton-nzm-technical-information-sheet](#)

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Mounting Method

Built-in device plug-in technique

#### Equipment heat dissipation, current-dependent

48 W

#### Number of auxiliary contacts (change-over contacts)

0

#### Number of auxiliary contacts (normally closed contacts)

0

#### Number of auxiliary contacts (normally open contacts)

0

#### Degree of protection

IP20

#### Electrical connection type of main circuit

Screw connection

Number of poles

Three-pole

Position of connection for main current circuit

Back side

Handle type

Rocker lever

Short delay current setting (Isd) - max

4000 A

Short delay current setting (Isd) - min

400 A

Instantaneous current setting (li) - max

4400 A

Instantaneous current setting (li) - min

800 A

Overload current setting (Ir) - max

400 A

Overload current setting (Ir) - min

200 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at

400/415 V, 50/60 Hz

65 kA