

# Eaton 168528

Catalog Number: 168528

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3 p, 220A, plug-in module

## General specifications



Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker electronic	168528
Model Code	NZMS3-ME220-SVE
EAN	Product Length/Depth
4015081650057	335 mm
Product Height	Product Width
215.2 mm	140 mm
Product Weight	Compliances
7.72 kg	RoHS conform

**Type**

Circuit breaker

**Amperage Rating**

220 A

**Voltage rating**

690 V - 690 V

**10.10 Temperature rise**

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 Short-circuit rating**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 Electromagnetic compatibility**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 Mechanical function**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.2 Corrosion resistance**

Meets the product standard's requirements.

**10.2.3.1 Verification of thermal stability of enclosures**

Meets the product standard's requirements.

**10.2.3.2 Verification of resistance of insulating materials to normal heat**

Meets the product standard's requirements.

**10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects**

Meets the product standard's requirements.

**10.2.4 Resistance to ultra-violet (UV) radiation**

Meets the product standard's requirements.

**10.2.5 Lifting**

Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 Mechanical impact**

Does not apply, since the entire switchgear needs to be evaluated.

**10.2.7 Inscriptions****Brochures**

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

**Catalogs**

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

**eCAD model**

[DA-CE-ETN.NZMS3-ME220-SVE](#)

**Installation instructions**

[IL01219023Z](#)

**Installation videos**

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

**mCAD model**

[nzmh3\\_me220\\_sve.dwg](#)

[nzmh3\\_me220\\_sve.stp](#)

**Technical data sheets**

[eaton-nzm-technical-information-sheet](#)

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Fitted with:

Thermal protection

#### Mounting Method

Built-in device plug-in technique

#### Equipment heat dissipation, current-dependent

14.52 W

#### Rated operating power at AC-3, 230 V

55 kW

#### Rated operating power at AC-3, 400 V

110 kW

#### Switch off technique

Electronic

#### Degree of protection

IP20

#### Direction of incoming supply

As required

Electrical connection type of main circuit

Screw connection

Number of poles

Three-pole

Functions

Phase failure sensitive

Handle type

Rocker lever

Instantaneous current setting (li) - max

3080 A

Instantaneous current setting (li) - min

440 A

Overload current setting (Ir) - max

220 A

Overload current setting (Ir) - min

110 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

65 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

65 kA

Rated short-circuit breaking capacity Icu (IEC/EN 60947) at 400/415 V, 50/60 Hz

65 kA

Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.