

# Eaton 115452

Catalog Number: 115452

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 63A, motor protection



Photo is representative

### General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker thermo-magnetic	115452
	Model Code
	NZMH1-M63
EAN	Product Length/Depth
4015081151929	88 mm
Product Height	Product Width
145 mm	90 mm
Product Weight	Compliances
1.037 kg	RoHS conform
Certifications	
IEC/EN 60947	
IEC	

## Type

Circuit breaker

## Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I<sub>cn</sub>)

Rated current = rated uninterrupted current: 63 A

Terminal capacity hint: Up to 95 mm<sup>2</sup> can be connected depending on the cable manufacturer.

With phase-failure sensitivity

Tripping class 10 A

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

## Application

Use in unearthed supply systems at 690 V

## Amperage Rating

63 A

## Voltage rating

690 V - 690 V

## Circuit breaker frame type

NZM1

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the

## Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

## Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

## Characteristic curve

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-058.eps](#)

[eaton-circuit-breaker-let-through-current-nzm-mccb-characteristic-curve-003.eps](#)

## Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[eaton-circuit-breaker-socket-nzm-mccb-3d-drawing.eps](#)

## Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

## mCAD model

[DA-CD-nzm1\\_3p](#)

[DA-CS-nzm1\\_3p](#)

## Technical data sheets

[eaton-nzm-technical-information-sheet](#)

switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Fitted with:

Thermal protection

#### Pollution degree

3

#### Mounting Method

Fixed

Built-in device fixed built-in technique

#### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

#### Equipment heat dissipation, current-dependent

14.88 W

#### Utilization category

A (IEC/EN 60947-2)

#### Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

70 °C

#### Ambient storage temperature - min

-40 °C

#### Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

#### Rated insulation voltage (Ui)

690 V

#### Rated operating power at AC-3, 230 V

18.5 kW

#### Rated operating power at AC-3, 400 V

30 kW

#### Switch off technique

Thermomagnetic

#### Degree of protection

IP20 (basic degree of protection, in the operating controls area)

IP20

#### Direction of incoming supply

As required

#### Electrical connection type of main circuit

Other

#### Lifespan, mechanical

20000 operations

#### Overvoltage category

III

#### Rated operational current

55 A (400 V AC-3)

#### Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

#### Degree of protection (terminations)

IP00 (terminations, phase isolator and strip terminal)

IP10 (tunnel terminal)

#### Number of poles

Three-pole

#### Terminal capacity (copper strip)

Max. 9 segments of 9 mm x 0.8 mm at box terminal

Min. 2 segments of 9 mm x 0.8 mm at box terminal

#### Lifespan, electrical

5000 operations at 690 V AC-3

7500 operations at 415 V AC-3

7500 operations at 690 V AC-1

7500 operations at 400 V AC-3

10000 operations at 400 V AC-1

10000 operations at 415 V AC-1

#### Functions

Phase failure sensitive

Motor protection

#### Shock resistance

20 g (half-sinusoidal shock 20 ms)

Rated operational current for specified heat dissipation ( $I_n$ )

63 A

Short-circuit release non-delayed setting - max

882 A

Short-circuit release non-delayed setting - min

504 A

Handle type

Rocker lever

Instantaneous current setting ( $I_i$ ) - max

882 A

Instantaneous current setting ( $I_i$ ) - min

504 A

Number of operations per hour - max

120

Overload current setting ( $I_r$ ) - max

63 A

Overload current setting ( $I_r$ ) - min

50 A

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 230 V, 50/60 Hz

100 kA

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 400/415 V, 50/60 Hz

35 kA

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 440 V, 50/60 Hz

35 kA

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 525 V, 50/60 Hz

10 kA

Rated short-circuit breaking capacity  $I_{cs}$  (IEC/EN 60947) at 690 V, 50/60 Hz

7.5 kA

Standard terminals

Box terminal

Optional terminals

Connection on rear. Screw terminal. Tunnel terminal

Release system

Thermomagnetic release

#### Short-circuit total breaktime

< 10 ms

#### Terminal capacity (aluminum solid conductor/cable)

16 mm<sup>2</sup> (1x) at tunnel terminal

#### Terminal capacity (aluminum stranded conductor/cable)

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at tunnel terminal

#### Terminal capacity (control cable)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)

#### Terminal capacity (copper busbar)

Max. 16 mm x 5 mm direct at switch rear-side connection

Min. 12 mm x 5 mm direct at switch rear-side connection

M6 at rear-side screw connection

#### Terminal capacity (copper solid conductor/cable)

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal

#### Terminal capacity (copper stranded conductor/cable)

6 mm<sup>2</sup> - 25 mm<sup>2</sup> (2x) at box terminal

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

10 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) at box terminal

10 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> (2x) direct at switch rear-side connection

#### Rated short-circuit breaking capacity I<sub>cu</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz

35 kA

#### Rated short-circuit making capacity I<sub>cm</sub> at 400/415 V, 50/60 Hz

220 kA

#### Rated short-circuit making capacity I<sub>cm</sub> at 440 V, 50/60 Hz

154 kA

#### Rated short-circuit making capacity I<sub>cm</sub> at 525 V, 50/60 Hz

40 kA

#### Rated short-circuit making capacity I<sub>cm</sub> at 690 V, 50/60 Hz

17 kA

#### Rated short-circuit making capacity I<sub>cm</sub> at 240 V, 50/60 Hz

220 kA

#### Rated impulse withstand voltage (U<sub>imp</sub>) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

6000 V

Power loss

14.9 W



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



Eaton.com/socialmedia