



Hovedkarakteristikk

Produktspekter	TeSys d TeSys D kontroll relé TeSys f
Serie	TeSys
Produkt eller komponent type	Hjelpekontakt blokk
Hjelpekontakt funksjon	Momentan
Kontakttype	2 NO + 2 NC
Tilkoblingsklemmer	Skrutilkobling 1 cable 1...2.5 mm ² - cable stiffness: fleksibel - med cable end Skrutilkobling 1 cable 1...2.5 mm ² - cable stiffness: fleksibel - uten cable end Skrutilkobling 1 cable 1...2.5 mm ² - cable stiffness: solid - med cable end Skrutilkobling 1 cable 1...2.5 mm ² - cable stiffness: solid - uten cable end Skrutilkobling 2 cable 1...2.5 mm ² - cable stiffness: fleksibel - med cable end Skrutilkobling 2 cable 1...2.5 mm ² - cable stiffness: fleksibel - uten cable end Skrutilkobling 2 cable 1...2.5 mm ² - cable stiffness: solid - med cable end Skrutilkobling 2 cable 1...2.5 mm ² - cable stiffness: solid - uten cable end

Alternativer

Montasjeplassering	Front
[Ui] isolasjonsspenning	690 V - conforming to IEC 60947-5-1 600 V - certifications CSA 600 V - certifications UL
[Ue] merkespenning	690 V AC 25...400 Hz
[Ith] fri luft termisk strøm	10 A på ≤ 60 °C
Irms rated making capacity	140 A på ≤ 690 V AC i samsvar med IEC 60947-5-1 250 A på ≤ 690 V DC i samsvar med IEC 60947-5-1
Permissible short-time rating	100 A at 60 °C 1 s 120 A at 60 °C 500 ms 140 A at 60 °C 100 ms
Beskyttelsestype	GG fuse ≤ 10 A rating according to operational current for Ue ≤ 690 V
Sikringsstørrelse	10 A gG IEC 60947-5-1
Mekanisk levetid	30 Mcycles
Minimum brytestrøm	5 mA
Minimum switching voltage	17 V
Non-overlap time	1.5 ms on de-energisation (no overlap between NC and NO contact) 1.5 ms on energisation (no overlap between NC and NO contact)
Overlap time	1.5 ms
Isolasjonsmotstand	> 10 MOhm
Vekt	0.05 kg
Farge	Red RAL 3000

Miljø

miljøegenskaper	Normale omgivelser
standarder	BS 4794 EN 60947-5-1 IEC 60947-5-1 NF C 63-140

	VDE 0660
produktsertifikater	CSA UL
IP-grad	IP2x i samsvar med VDE 0106
protective treatment	TH i samsvar med IEC 60068
omgivelsestemperatur drift	-5...60 °C
omgivelsestemperatur for lagring	-60...80 °C
operating altitude	3000 m uten derating in temperature

Bærekraftig

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0629 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering