



SAGA™ COVER PLATES

PEP ecopassport® Product Environmental Profile





Document in compliance with ISO 14025: 2006 "Environmental labels and declarations. Type III environmental declarations

pia.denninghoff@de.abb.com				
WEBSITE				
www.busch-jaeger.de/en/online-catalogue				
LANG.	PAGE			
1 en	1/12			
	LANG. 1 en			

ABB Purpose & Embedding Sustainability

ABB is committed to continually promoting and embedding sustainability across its operations and value chain, aspiring to become a role model for others to follow. With its ABB Purpose, ABB is focusing on reducing harmful emissions, preserving natural resources and championing ethical and humane behavior.



General Information

Reference product	Mechanical Timer 0-15min (2CKA001753A9986; variation 6)
Description of the product	The product family covered in this study is called SAGA [™] Cover Plates. It is a cover plate used to cover the socket insert together with the relevant design frame. It is designed for indoor use only and is installed manually. The product is a white square, which is mainly made of polycarbonate and steel.
Functional unit	Protect users during 20 years against direct contact with live parts, with a protection class IP and IK.
Other products covered	Variation 1: Adapter frame 50x50mm (2CKA001726A0239); Variation 2: Center plate for TV/R/SAT (2CKA001724A4428); Variation 3: Center plate for TV/R (2CKA001724A4459); Variation 4: Dimmer control element with neon light (2CKA006599A3048; covered in a separate PEP); Variation 5: Mechanical Timer 0-120 min (2CKA001753A9987); Variation 7: Center plate for 22,5mm devices (2CKA001724A4429); Variation 8: Center plate for USB-Charger (2CKA001724A4430)

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	2/12



STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	3/12

Additional Environmental Information

Manufacturing	The SAGA [™] Cover Plates are produced at and delivered from two internal BJE sites in Germany. One site is in Lüdenscheid and the other one in Bad Berleburg/Aue. For this product family, all production steps happen in Bad Berleburg/Aue, and only the final distribution happens from Lüdenscheid. No recycled material content is assumed. All components are transported by lorry from the supplier to these two manufacturing sites. The manufacturing waste for all materials is included. The values are as follows, based on BJE expert knowledge: 2,9% for metal, 2% for paper and cardboard, 2% for metal, and 30% for all remaining materials (based on chapter 3.1.5.1.2 of PSR-0005-ed3). The energy BJE in Bad Berleburg/Aue purchases for the manufacturing consists of 82% hydropower and 18% CHP. However, to avoid double counting of renewable energy, a dataset for the German market mix for electricity was used instead of a hydropower dataset. The amount of natural gas for both on-site electricity generation (CHP) and heating, as well as the emissions of both was used as an input to the model. All CO2 emissions are compensated through ClimatePartner, but this compensation is not accounted for in the EPD. For transport of waste from the manufacturing site to the treatment facility, the default distance of 100 km by truck is used, in line with chapter 3.1.5.1.2 of PSR-0005-ed3. Specific one-year data from 2022 on manufacturing site level was collected and allocated to the products components which are manufactured in-house by mass allocation following the requirements of ISO 14044.
Distribution	The transport scenario is estimated based on the distance to the capital city of the countries it is sold to, according to the sales data for 2022.
Installation	Installation is done manually without using energy or other auxiliary materials. Treatment of packaging waste is included in this stage, assuming the European end-of-life scenario mentioned in chapter 5.1.5.2.1 of the PSR.
Use	The SAGA [™] Cover Plates are aesthetic protective covers and do not require any electricity for their main function.
End of life	The standard scenario set in the PCR is considered.
Benefits and loads beyond the system boundaries	Steel has a recovery rate of 80% according to the PCR. The Module D formula from the PCR was used to calculate the benefits of these components. Other materials were not included here, due to a material recovery rate of 0. For the product packaging, the default (European) end-of-life data from chapter 3.1.5.2.1 of the PSR is used to determine the recycling rates. According to that, cardboard has a recovery rate of 82% and plastic has one of 41%, which are also included in this stage.

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	4/12

Environmental Impacts

End of life

Reference lifetime	20 years
Product category	3.13 "Other equipment"
Installation elements	Not applicable
Use scenario	Not applicable
Geographical representativeness	Production site data is for Germany, and all other data has a European scope.
Technological representativeness	Materials and process data are specific for the production of the SAGA™ Cover Plates.
Software and database used	SimaPro 9.4.0.2., ecoinvent 3.9.1, PEF 3.0
Energy model used	
Manufacturing	Electricity, high voltage {DE} market for Cut-off, U Electricity, low voltage {DE} electricity production, photovoltaic, 3kWp slanted-roof installation, single-Si, panel, mounted Cut-off, U Natural gas, high pressure {DE} market for Cut-off, S
Installation	Not applicable
Use	Not applicable

Approved Public ABBG-00280-V01.01-EN 1 en 5/12	STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
	Approved	Public	ABBG-00280-V01.01-EN	1	en	5/12

Not applicable



Common base of mandatory indicators

% Environmental Impact per Life Cycle Stage of Reference Product

Environmental impact indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
GWP-total	kg CO ₂ eq	2,21E-01	1,66E-01	1,05E-02	1,24E-02	0,00E+00	3,24E-02	-7,21E-03
GWP-fossil	kg CO ₂ eq	2,10E-01	1,65E-01	1,05E-02	3,66E-03	0,00E+00	3,13E-02	-8,33E-03
GWP-biogenic	kg CO ₂ eq	9,05E-03	-7,90E-04	8,36E-06	8,77E-03	0,00E+00	1,06E-03	1,24E-03
GWP-luluc	kg CO ₂ eq	1,78E-03	1,77E-03	4,71E-06	2,16E-07	0,00E+00	1,23E-06	-8,06E-05
GWP-fossil = Globa GWP-biogenic = Gl GWP-luluc = Globa	al Warming Po obal Warming I Warming Po	otential fossil Potential bi tential land u	fuels ogenic use and land us	e change				
ODP	kg CFC-11 eq.	2,35E-08	2,32E-08	2,22E-10	1,23E-11	0,00E+00	4,95E-11	-1,97E-10
ODP = Depletion po	otential of the	stratospheric	c ozone layer					
AP	H+ eq.	6,31E-04	5,85E-04	3,18E-05	2,60E-06	0,00E+00	1,23E-05	-3,80E-05
AP = Acidification p	otential, Accu	mulated Exc	eedance					
EP-freshwater	kg P eq.	7,36E-06	7,23E-06	8,03E-08	7,75E-09	0,00E+00	4,27E-08	-4,75E-07
EP-marine	kg N eq.	1,45E-04	1,28E-04	1,08E-05	1,08E-06	0,00E+00	5,21E-06	-1,60E-05
EP-terrestrial	mol N eq.	1,45E-03	1,27E-03	1,15E-04	1,13E-05	0,00E+00	5,14E-05	-1,08E-04
EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment EP-terrestrial = Eutrophication potential, Accumulated Exceedance								
POCP	kg NMVOC	6,65E-04	6,00E-04	4,77E-05	3,07E-06	0,00E+00	1,48E-05	-3,78E-05
POCP = Formation	potential of tr	opospheric o	zone					
ADP-minerals & metals	kg Sb eq.	8,60E-07	8,20E-07	3,26E-08	9,63E-10	0,00E+00	6,13E-09	-3,63E-08
ADP-fossil	MJ	3,85E+00	3,68E+00	1,44E-01	3,96E-03	0,00E+00	2,11E-02	-1,22E-01
ADP-minerals & me ADP-fossil = Abiotic	etals = Abiotic c depletion for	depletion po fossil resour	tential for non-f	ossil resources				
WDP	m³ eq. depr	5,68E-02	5,43E-02	5,52E-04	2,41E-04	0,00E+00	1,72E-03	-3,29E-03
WDP = Water Depr	vivation potent	ial						
STATUS	SEC		-	REGISTRATION	NUMBER	REV.	LANG.	PAGE
Approved	Pub	lic		ABBG-00280-V07	1.01-EN	1	en	6/12

Common base of mandatory indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
PERE	MJ	1,94E-01	1,89E-01	2,51E-03	4,94E-04	0,00E+00	1,53E-03	-6,84E-03
PERM	MJ	4,68E-02	4,68E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	-3,76E-02
PERT	MJ	2,41E-01	2,36E-01	2,51E-03	4,94E-04	0,00E+00	1,53E-03	-4,45E-02
PENRE	MJ	3,83E+00	3,66E+00	1,44E-01	3,96E-03	0,00E+00	2,11E-02	-1,22E-01
PENRM	MJ	1,94E-02	1,94E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	-7,37E-04
PENRT	MJ	3,85E+00	3,68E+00	1,44E-01	3,96E-03	0,00E+00	2,11E-02	-1,22E-01

Inventory flows indicator - Resource use indicators

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials

PERM = Use of renewable primary energy resources used as raw materials

PERT = Total Use of renewable primary energy resources

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials

PENRM = Use of non-renewable primary energy resources used as raw materials

PENRT = Total Use of non-renewable primary energy resources

Inventory flows indicator – Indicators describing the use of secondary materials, water, and energy resources

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
SM	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m³	1,64E-03	1,56E-03	2,08E-05	7,73E-06	0,00E+00	5,42E-05	-9,50E-05

SM = Use of secondary material

RSF = Use of renewable secondary fuels

NRSF = Use of non-renewable secondary fuels

FW = Use of net fresh water

Inventory flows indicator - Waste category indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
Hazardous waste disposed	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Non- hazardous waste	kg	1,95E-02	0,00E+00	0,00E+00	1,01E-03	0,00E+00	1,85E-02	0,00E+00
Radioactive waste disposed	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	7/12

Common base of mandatory indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
Components for re- use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	8,58E-03	2,93E-03	0,00E+00	4,59E-03	0,00E+00	1,06E-03	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

Inventory flows indicator – Output flow indicators

Inventory flow indicator – other indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
Biogenic carbon content of the product	kg of C	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Biogenic carbon content of the associated packaging	kg of C	0,00E+00	-2,54E-03	0,00E+00	2,54E-03	0,00E+00	0,00E+00	0,00E+00

Approved Public ABBG-00280-V01.01-EN 1 en 8/12	STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
	Approved	Public	ABBG-00280-V01.01-EN	1	en	8/12

Optional indicators

Environmental indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
Total use of primary energy during the life cycle	MJ	4,09E+00	3,92E+00	1,46E-01	4,45E-03	0,00E+00	2,26E-02	-1,67E-01
Emissions of fine particles	incidence of diseases	7,12E-09	5,97E-09	6,95E-10	2,63E-11	0,00E+00	4,27E-10	-5,31E-10
lonizing radiation, human health	kBq U235 eq.	3,90E-03	3,75E-03	8,44E-05	5,79E-06	0,00E+00	5,76E-05	-2,16E-04
Ecotoxicity (fresh water)	CTUe	4,09E+00	3,93E+00	7,71E-02	1,15E-02	0,00E+00	7,06E-02	-5,53E-02
Human toxicity, car- cinogenic effects	CTUh	2,14E-10	1,74E-10	4,28E-12	6,78E-13	0,00E+00	3,56E-11	-1,79E-11
Human toxicity, non- carcinogenic effects	incidence of diseases	8,63E-09	8,33E-09	1,26E-10	2,79E-11	0,00E+00	1,45E-10	-1,24E-10
Impact related to land use/soil quality		8,32E-01	7,44E-01	7,36E-02	3,12E-03	0,00E+00	1,04E-02	-2,05E-01

Other indicators

Indicator	Unit	Total	Manu- facturing	Distri- bution	Installation	Use	End of life	Bene- fits
No Other indicators used								

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	9/12

Extrapolation Factors

For other products than the Reference product covered by this PEP, the environmental impacts for each phase of the lifecycle are obtained by multiplying the values of the Reference product by the following coefficients:

* if the coefficient is "1", the impacts of the phase of the life cycle are assimilated to the Reference product, meaning that the impacts are unchanged in comparison to the Reference product

Product name	Manu- facturing	Distri- bution	Installation	Use	End of life	Benefits
Adapter frame 50x50mm	0,18	0,24	0,49	-	0,15	0,00
Center plate for TV/R/SAT	0,61	0,92	1,74	-	0,62	1,41
Center plate for TV/R	0,62	0,90	1,64	-	0,63	1,41
Mechanical Timer 0-120 min	0,91	0,89	1,00	-	0,85	1,00
Mechanical Timer 0- 15min	1,00	1,00	1,00	-	1,00	1,00
Center plate for 22,5mm devices	0,54	1,38	1,01	-	1,51	14,64
Center plate for USB- Charger	0,52	0,68	1,18	-	0,49	0,66

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	10/12

Environmental Impact Indicator Glossary

Impact indicators

Indicator	Description	Distri- bution
Global warming potential (GWP) - total	Indicator of potential global warming caused by emissions to air contributing to the greenhouse effect. The total global warming potential (GWP-total) is the sum of three sub- categories of climate change. GWP-total = GWP-fossil + GWP-biogenic + GWP- land use and land use change	kg CO₂ eq.
Ozone depletion (ODP)	Emissions to air that contribute to the destruction of the stratospheric ozone layer	kg CFC- 11 eq.
Acidification of soil and water (A)	Acidification of soils and water caused by the release of certain gases to the atmosphere, such as nitrogen oxides and sulphur oxides	H+ eq.
Eutrophication (E)	Indicator of the contribution to eutrophication of water by the enrichment of the aquatic ecosystem with nutritional elements, e.g. industrial or domestic effluents, agriculture, etc. This indicator is divided to three: freshwater, marine and terrestrial.	kg P eq., kg N eq., mole N eq.
Photochemical ozone creation (POCP)	Indicator of emissions of gases that affect the creation of photochemical ozone in the lower atmosphere (smog) because of the rays of the sun.	kg NMVOC eq.
Depletion of abiotic resources – elements (ADPe)	Indicator of the depletion of natural non-fossil resources	kg Sb eq.
Depletion of abiotic resources – fossil fuels (ADPf)	The use of non-renewable fossil resources in an unsustainable way (e.g. from material to waste)	MJ (lower heating value)
Water Deprivation potential (WDP)	Deprivation-weighted water consumption. Assesses the potential of water deprivation, to either humans or ecosystems, building on the assumption that the less water remaining available per area, the more likely another user will be deprived.	m³ eq. depr.

Resource use indicators

Indicator	Description	Distri- bution
Total use of primary energy	Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials) + Total use of renewable primary energy re- sources (primary energy and primary energy resources used as raw materials)	MJ (lower heating value)

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	11/12

Drafting Rules:	PCR-ed4-EN-2021 09 06					
Supplemented by:	PSR-0005-ed3-EN-2023 06 06					
Information and refe documents:	ference www.pep-ecopassport.org					
Validity period: 5 ye	ars					
Independent verification of the declaration and data, in compliance with ISO 14025: 2006						
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)						
PEP are compliant with XP C08-100-1:2016 and EN 50693:2019 or NF E38-500 :2022 The elements of the present PEP cannot be compared with elements from any other program.						
ental labels and declarati	ons. Type III					
	Drafting Rules: Supplemented by: Information and refe documents: Validity period: 5 ye compliance with ISO 140 ompliance with ISO 140 compliance of the second second second compliance of the second					

STATUS	SECURITY LEVEL	REGISTRATION NUMBER	REV.	LANG.	PAGE
Approved	Public	ABBG-00280-V01.01-EN	1	en	12/12