

EMERGENCY LIGHTS | SERIE SLX



SLX EL LED HIGH COVER 3h 32m IR SM

ITEM NUMBER EN10077203 |
GTIN 4015120077203



- Single-battery emergency light for escape route signage with 3 h emergency light duration for 32m viewing distance
- Self-monitoring with coloured status indicator
- Tamper-resistant function check can be executed by remote control or magnet
- Optionally, operation in continuous or stand-by mode possible

TECHNICAL DATA

GENERAL

Device category	Escape sign light
Product information	For indoor use only.



GENERAL

Included in delivery	Includes 6 self-adhesive symbol sheets with 32 m viewing distance (right, left, 2 x upwards and 2 x downwards arrows) and rechargeable battery
----------------------	--

Remote controllable

Conformity	CE, EAC, RoHS, WEEE
------------	---------------------

Warranty	5 years
----------	---------

MOUNTING

Installation type	Surface mounting
-------------------	------------------

Installation position	Ceiling / wall
-----------------------	----------------

Installation dimension	Installation length: 430 mm x Installation width: 155 mm x Installation depth: 66 mm,
------------------------	---

Type of connection	Push terminal
--------------------	---------------

HOUSING

Dimensions	Length 388 mm x Width 148 mm x Height/Depth 231 mm
------------	---

Weight	875 g
--------	-------

Material	UV-stabilised polycarbonate
----------	-----------------------------

Protection type	IP54
-----------------	------

Permissible ambient temperature	5 °C...+35 °C
---------------------------------	---------------

Colour	white, similar to RAL 9016
--------	----------------------------

ELECTRICAL VERSION

Control system	ON/OFF
----------------	--------

ELECTRICAL VERSION

Protection class II

Nominal voltage 230 V ~ / 50 Hz

LIGHT

Light emission direct

Rated output P 3 W

* Industry standard value for the average rated life. Alternative values for specific project tenders as well as the mandatory lifetime values for all included light sources in accordance with the ecodesign directive (L70B50) can be found in the data sheet.

EMERGENCY LIGHTING

Viewing distance 32 m

Symbol height 160 mm

Light duration 3 h

Switching type Continuous mode/standby mode

Power feed Decentralised (single-battery)

Battery NiCd 3,6 V / 0,8 Ah

Charging time 20 hours min.

Status display by LED

DOWNLOADS

GENERAL All files as ZIP 

Data sheet PDF 

Declaration of conformity PDF 

LIGHT AND BUILDING PLANNING

LIGHT AND BUILDING PLANNING

Planning data BIM

INSTALLATION

Short instruction

PDF



TENDER SPECIFICATIONS

Invitation to tender text neutral
(rtf)

RTF



Invitation to tender text neutral
(x81)

X81



Tender text with leading brand

RTF



ACCESSORIES

MOUNTING



SLX/ELX MOUNTING FRAME 430 FM

Item number **EN10077234**

Installation frame for SLX and ELX series, installation hole size 430 x 155 mm



SLX/ELX TUBE PENDULUM SET

Item number **EN10078316**

Conduit pendulum set for SLX and ELX series



SLX/ELX WALL BRACKET 110

Item number **EN10077289**

Wall bracket mounting for SLX and ELX series, 110 mm length



PROTECTION



SLX/ELX BASKET GUARD CEILING

Item number **EN1007296**

Basket guard for SLX and ELX series, 260 mm high



REMOTE CONTROL



ESY-Pen

Item number **EP10425356**

ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management



SYMBOL



SLX 32 HIGH COVER SYMBOL SET II

Item number **EN10077531**

Symbol set for SLX series, High Cover, 32 m, detection range right upwards, left upwards, right downwards, left downwards



SPARE PARTS

BATTERY



SLX BATTERY NiCd 800mAh

Item number **EN10077401**

NiCd rechargeable battery (3.6V/800 mAh) for SLX series with reverse polarity protected plug-in connection



SYMBOL



SLX 32 HIGH COVER SYMBOL SET I

Item number **EN10077524**

Symbol set for SLX series, High Cover, 32 m detection range right, left, upwards, downwards



PLANNING DATA BIM

Use the
BIM
portal for
efficient
digital
planning!

SLX/ELX SERIES

Discover
the full
potential
of the
SLX/ELX
series.

Discover

our
complete
product
range.

LOGUE
2024/2025

ESYLUX

ESY-PEN
AND ESY
APP!

easy
parameterisation,
remote control
and
documentation.



SIMILAR PRODUCTS

OTHER PRODUCTS

OLIVIA
MOISTURE-PROOF LIGHTS



OLIVIA-2
MOISTURE-PROOF LIGHTS



SLP-2
PORTABLE SPOTLIGHT





COMPACT
PRESENCE AND MOTION
DETECTORS



COMPACT
EXPRESS
PRESENCE AND MOTION
DETECTORS



STANDARD
PRESENCE AND MOTION
DETECTORS



SERVICE

Downloads

Catalogues and brochures

Videos

Tender specifications

KNX product database

Mobile apps

Knowledge

Academy & Training

Name concept

Online Demo ESY-App

Covers for wall detectors

Ecodesign Directive

Presence and Motion detectors

Support

Planning & project support

BIM-Portal

ESYLUX Services

ESYCOMPARE

SOLUTIONS

Offices

Group offices
Open-plan office
Meeting rooms
Reversible offices
Communal areas

Education

Classrooms
Break rooms
Mensas

Daycare centers

Playrooms

Health Care

Patient rooms
Examination rooms
Multi-purpose rooms
Canteens

Outdoor areas

Pathways and entrances
Multi-storey car parks
Outdoor car parks

Secondary areas

Corridors
Staircases
Side rooms
Sanitary facilities

PRODUCTS

Indoor automation

Presence and motion detectors
Brightness controller
Controls
Smoke alarm

Indoor lighting

Lighting systems
Recessed lights
Wall and ceiling lights
Downlights
Moisture-proof lights
Emergency lights
Portable spotlight

Outdoor automation

Motion detectors
Twilight switch

Outdoor lighting

Wall lights
Up-/Downlights
Bollard lights
Floodlights

HIGHLIGHTS

ALVA
SVENJA
Emergency Lights
CELINE-2
SLP-2
ATMO
Downlights

Downlights

Outdoor Floodlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

FLAT

OLIVIA-2

Switch lights on and off
hygienically

Focus products Q2/2024

INNOVATIONS

Demand-driven Automation

Intelligent Lighting

Human Centric Lighting

Light control with DALI-2

COMPANY

Vision and mission

Experience and quality

Corporate responsibility

Research and development

Cooperations and
memberships

Awards and prizes

References

PRESS

Press releases

Images

ESYWORLD

Imprint

Privacy policy

Privacy settings

Whistleblowing

General terms and
conditions

Guarantee

Disclaimer

Contact

© 2024 ESYLUX GmbH

