

TECHNICAL DATA

DOWNLOADS ACCESSORIES PARTS

SPARE

BIM

EMERGENCY LIGHTS | SERIE SLX





SLX EL LED DISPLAY 8h 32m IR SM

ITEM NUMBER EN10077319 GTIN 4015120077319

- Single-battery emergency light for escape route signage with 8 h emergency light duration for 32m viewing distance
- Self-monitoring with coloured status indicator
- Tamper-resistant function check can be executed by remote control or magnet
- Optionally, operation in continuous or stand-by mode possible

TECHNICAL DATA

GENERAL

Device category	Escape sign light
Product information	For indoor use only.
Included in delivery	Symbol panel (display) YEARS WARRANTY included. Please order as an accessory.

MOUNTING Installation type Sur Installation position Ce Installation dimension Ins Ins Ins Ins Ins Very of connection Pus HOUSING Dimensions Ler He Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 of	ace mounting ing / wall allation length: 430 mm x allation width: 155 mm x allation depth: 66 mm, aterminal gth 388 mm x Width 148 mm x ght/Depth 223 mm
MOUNTING Installation type Sull Installation position Ce Installation dimension Installat	ace mounting ing / wall allation length: 430 mm x allation width: 155 mm x allation depth: 66 mm, aterminal gth 388 mm x Width 148 mm x ght/Depth 223 mm
Installation position Ce Installation dimension Ins	ing / wall allation length: 430 mm x allation width: 155 mm x allation depth: 66 mm, n terminal gth 388 mm x Width 148 mm x ght/Depth 223 mm
Installation position Ce Installation dimension Ins	ing / wall allation length: 430 mm x allation width: 155 mm x allation depth: 66 mm, n terminal gth 388 mm x Width 148 mm x ght/Depth 223 mm
Installation dimension Installation dimension Installation dimension Installation dimension Installation dimensions Installation Pust Inst	allation length: 430 mm x allation width: 155 mm x allation depth: 66 mm, n terminal gth 388 mm x Width 148 mm x
Type of connection Pus HOUSING Dimensions Let He Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 °	allation width: 155 mm x allation depth: 66 mm, n terminal gth 388 mm x Width 148 mm x
Type of connection Pus HOUSING Dimensions Ler He Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 °	allation width: 155 mm x allation depth: 66 mm, n terminal gth 388 mm x Width 148 mm x
HOUSING Dimensions Let He Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 °	gth 388 mm x Width 148 mm x ght/Depth 223 mm
Dimensions Let He Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 °	ht/Depth 223 mm
Weight 770 Material UV Protection type IP2 Permissible ambient temperature 5 °	ht/Depth 223 mm
Material UV Protection type IP2 Permissible ambient temperature 5 °	g
Protection type IP2 Permissible ambient temperature 5°	
Permissible ambient temperature 5 °	stabilised polycarbonate
Permissible ambient temperature 5 °	
Colour wh	+35°C
	e, similar to RAL 9016
ELECTRICAL VERSION	
Control system ON	OFF
Protection class II	
Nominal voltage 236	

17.5 A / 208 µs

In-rush current

Leakage current	0.01 mA	
LIGHT		
Light emission	direct	

Rated output P	3 W

^{*} Industry standard value for the average rated life. Alternative values for specific project tenders as well as the mandatory lifetime values for all included light sources in accordance with the ecodesign directive (L70B50) can be found in the data sheet.

EMERGENCY LIGHTING

Viewing distance	32 m
Symbol height	160 mm
Light duration	8 h
Switching type	Continuous mode/standby mode

Powerfeed	Decentralised (single-battery)
Battery	NiCd3,6V/0,8Ah
Charging time	20 hours min.
Status display	by LED

DOWNLOADS

GENERAL		All files as ZIP	<u>▼</u>
Data sheet	PDF		<u>*</u>
Declaration of conformity	PDF		<u>*</u>

LIGHT AND BUILDING PLANNING

Planning	ata BIM		X

INSTALLATION

INSTALLATION

Short instruction	PDF	<u>*</u>

TENDER SPECIFICATIONS		
Invitation to tender text neutral (rtf)	RTF	<u>•</u>
Invitation to tender text neutral (x81)	X81	<u>*</u>
Tender text with leading brand	RTF	<u>•</u>

ACCESSORIES

MOUNTING



PROTECTION



SLX/ELX BASKET GUARD CEILING

Item number EN10077296

Basket guard for SLX and ELX series, 260 mm high









REMOTE CONTROL



ESY-Pen

Item number EP10425356 ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management











SYMBOL



SLX 32 DISPLAY SYMBOL 1-SIDE DOWN

Item number EN10079023

One-sided pictogram panel with 32 m detection range











SLX 32 DISPLAY SYMBOL 1-SIDE LEFT

Item number EN10079016

One-sided pictogram panel with 32 m detection

range











SLX 32 DISPLAY SYMBOL 1-SIDE RIGHT

Item number EN10079009

One-sided pictogram panel with 32 m detection range





SLX 32 DISPLAY SYMBOL 1-SIDE TOP

Item number EN10032509

One-sided pictogram panel with 32 m detection







72h **±** ♠ < >

SLX 32 DISPLAY SYMBOL 2-SIDE DOWN

Item number EN10079030

Two-sided pictograph panel with 32 m detection

range











SLX 32 DISPLAY SYMBOL 2-SIDE DOWN **RIGHT LEFT**

Item number EN10032530

Two-sided pictogram panel with 32 m detection

range











SLX 32 DISPLAY SYMBOL 2-SIDE RIGHT

Item number EN10079047

Two-sided pictograph panel with 32 m detection

range











SLX 32 DISPLAY SYMBOL 2-SIDE TOP **RIGHT LEFT**

Item number EN10032523

Two-sided pictogram panel with 32 m detection

range











SPARE PARTS

BATTERY



Item number EN10077401

NiCd rechargeable battery (3.6V/800 mAh) for SLX series with reverse polarity protected plug-in

connection















SIMILAR PRODUCTS

OTHER PRODUCTS

OLIVIA MOISTURE-PROOF LIGHTS
OLIVIA-2
MOISTURE-PROOF LIGHTS
SLP-2 PORTABLE SPOTLIGHT
>
COMPACT PRESENCE AND MOTION DETECTORS
COMPACT EXPRESS
PRESENCE AND MOTION DETECTORS
STANDARD PRESENCE AND MOTION DETECTORS





SERVICE

Downloads

Catalogues and brochures

Videos

Tender specifications

KNX product database

Mobile apps

Knowledge

Academy & Training

Name concept

Online Demo ESY-App

Covers for wall detectors

Ecodesign Directive

Presence and Motion detectors

Support

Planning & project support

BIM-Portal

ESYLUX Services

ESYCOMPARE

ESYWORLD

SOLUTIONS

Offices

Group offices

Open-plan office

Meeting rooms

Reversible offices

Communal areas

Education

Classrooms

Break rooms

Mensas

Daycare centers

Playrooms

Health Care

Patient rooms

Examination rooms

Multi-purpose rooms

Canteens

Outdoor areas

Pathways and entrances

Multi-storey car parks

Outdoor car parks

Secondary areas

Corridors

Staircases

Side rooms

Sanitary facilities

PRODUCTS

Indoor automation

Presence and motion detectors

Brightness controller

Controls

Smoke alarm

Indoor lighting

Lighting systems

Recessed lights

Wall and ceiling lights

Downlights

Moisture-proof lights

Emergency lights

Portable spotlight

Outdoor automation

Motion detectors

Twilight switch

Outdoor lighting

Wall lights

Up-/Downlights

Bollard lights

Floodlights

HIGHLIGHTS

ALVA

SVENJA

Emergency Lights

CELINE-2

SLP-2

OMTA

Downlights

Outdoor Floodlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

FLAT

OLIVIA-2

Switch lights on and off hygienically

Focus products Q2/2024

INNOVATIONS

Demand-driven Automation Intelligent Lighting Human Centric Lighting Light control with DALI-2

COMPANY

Vision and mission Experience and quality Corporate responsibility Research and development Cooperations and memberships Awards and prizes References

PRESS

Press releases

Images

Imprint Privacy policy Privacy settings Whistleblowing General terms and conditions Guarantee Disclaimer Contact © 2024 ESYLUX GmbH











