

EMERGENCY LIGHTS |
 SERIE SLX

72h




SLX EL LED DISPLAY 3h 32m IR SM

ITEM NUMBER EN10077210 |

GTIN 4015120077210



- Single-battery emergency light for escape route signage with 3 h emergency light duration for 32m viewing distance
- Self-monitoring with coloured status indicator
- Tamper-resistant function check can be executed by remote control or magnet
- Optionally, operation in continuous or stand-by mode possible

TECHNICAL DATA

GENERAL

Device category	Escape sign light
Product information	For indoor use only.
Included in delivery	Symbol panel (display) 5 YEARS MANUFACTURER WARRANTY included. Please order as an accessory.

Remote controllable	
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

MOUNTING

Installation type	Surface mounting
Installation position	Ceiling / wall

Installation dimension	Installation length: 430 mm x Installation width: 155 mm x Installation depth: 66 mm,
Type of connection	Push terminal

HOUSING

Dimensions	Length 388 mm x Width 148 mm x Height/Depth 223 mm
Weight	725 g
Material	UV-stabilised polycarbonate

Protection type	IP20
Permissible ambient temperature	5 °C...+35 °C
Colour	white, similar to RAL 9016

ELECTRICAL VERSION

Control system	ON/OFF
Protection class	II
Nominal voltage	230 V ~ / 50 Hz

In-rush current	17.5 A / 208 µs
-----------------	-----------------

Leakage current	0.01 mA
-----------------	---------

LIGHT

Light emission	direct
----------------	--------

Rated output P	3 W
----------------	-----

* Industry standard value for the average rated life. Alternative values for specific project tenders as well as the mandatory lifetime values for all included light sources in accordance with the ecodesign directive (L70B50) can be found in the data sheet.

EMERGENCY LIGHTING

Viewing distance	32 m
------------------	------

Symbol height	160 mm
---------------	--------

Light duration	3 h
----------------	-----

Switching type	Continuous mode/standby mode
----------------	------------------------------

Power feed	Decentralised (single-battery)
------------	--------------------------------

Battery	NiCd 3,6 V / 0,8 Ah
---------	---------------------

Charging time	20 hours min.
---------------	---------------

Status display	by LED
----------------	--------

DOWNLOADS

GENERAL

All files as ZIP



Data sheet	PDF	
------------	-----	--

Declaration of conformity	PDF	
---------------------------	-----	--

LIGHT AND BUILDING PLANNING

Planning data BIM	
-------------------	--

INSTALLATION

INSTALLATION

Short instruction	PDF	
-------------------	-----	---

TENDER SPECIFICATIONS

Invitation to tender text neutral (rtf)	RTF	
Invitation to tender text neutral (x81)	X81	
Tender text with leading brand	RTF	

ACCESSORIES

MOUNTING



SLX/ELX MOUNTING FRAME 430 FM

Item number **EN10077234**
Installation frame for SLX and ELX series, installation hole size 430 x 155 mm



SLX/ELX TUBE PENDULUM SET

Item number **EN10078316**
Conduit pendulum set for SLX and ELX series



SLX/ELX WALL BRACKET 110

Item number **EN10077289**
Wall bracket mounting for SLX and ELX series, 110 mm length



PROTECTION



SLX/ELX BASKET GUARD CEILING

Item number **EN10077296**

Basket guard for SLX and ELX series, 260 mm high



REMOTE CONTROL



ESY-Pen

Item number **EP10425356**

ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management



SYMBOL



SLX 32 DISPLAY SYMBOL 1-SIDE DOWN

Item number **EN10079023**

One-sided pictogram panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 1-SIDE LEFT

Item number **EN10079016**

One-sided pictogram panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 1-SIDE RIGHT

Item number **EN10079009**

One-sided pictogram panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 1-SIDE TOP

Item number **EN10032509**

One-sided pictogram panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 2-SIDE DOWN

Item number **EN10079030**

Two-sided pictograph panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 2-SIDE DOWN RIGHT LEFT

Item number **EN10032530**

Two-sided pictogram panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 2-SIDE RIGHT LEFT

Item number **EN10079047**

Two-sided pictograph panel with 32 m detection range



SLX 32 DISPLAY SYMBOL 2-SIDE TOP RIGHT LEFT

Item number **EN10032523**

Two-sided pictogram panel with 32 m detection

range



SPARE PARTS

BATTERY



SLX BATTERY NiCd 800mAh

Item number **EN10077401**

NiCd rechargeable battery (3.6V/800 mAh) for SLX series with reverse polarity protected plug-in connection



PLANNING DATA BIM

Use the
BIM
portal for
efficient
digital
planning!



SLX/ELX SERIES

Discover
the full
potential
of the
SLX/ELX
series.

Discover

our
complete
product
range.

LOGUE

2024/2025

**ESY-PEN
AND ESY
APP!**

easy
parameterisation,
remote control
and
documentation.



SIMILAR PRODUCTS

OTHER PRODUCTS

OLIVIA
MOISTURE-PROOF LIGHTS



OLIVIA-2
MOISTURE-PROOF LIGHTS




SLP-2
PORTABLE SPOTLIGHT





COMPACT PRESENCE AND MOTION DETECTORS



COMPACT EXPRESS PRESENCE AND MOTION DETECTORS



STANDARD PRESENCE AND MOTION DETECTORS



SERVICE

Downloads

Catalogues and brochures

Videos

Tender specifications

KNX product database

Mobile apps

Knowledge

Academy & Training

Name concept

Online Demo ESY-App

Covers for wall detectors

Ecodesign Directive

Presence and Motion detectors

Support

Planning & project support

BIM-Portal

ESYLUX Services

ESYCOMPARE

ESYWORLD

SOLUTIONS

Offices

Group offices

Open-plan office

Meeting rooms

Reversible offices

Communal areas

Education

Classrooms

Break rooms

Mensas

Daycare centers

Playrooms

Health Care

Patient rooms

Examination rooms

Multi-purpose rooms

Canteens

Outdoor areas

Pathways and entrances

Multi-storey car parks

Outdoor car parks

Secondary areas

Corridors

Staircases

Side rooms

Sanitary facilities

PRODUCTS

Indoor automation

Presence and motion detectors

Brightness controller

Controls

Smoke alarm

Indoor lighting

Lighting systems

Recessed lights

Wall and ceiling lights

Downlights

Moisture-proof lights

Emergency lights

Portable spotlight

Outdoor automation

Motion detectors

Twilight switch

Outdoor lighting

Wall lights

Up-/Downlights

Bollard lights

Floodlights

HIGHLIGHTS

ALVA

SVENJA

Emergency Lights

CELINE-2

SLP-2

ATMO

Downlights

Outdoor Floodlights

ESYLUX Light Control

DEFENSOR

COMPACT
ESY-Pen
FLAT
OLIVIA-2
Switch lights on and off
hygienically
Focus products Q2/2024

INNOVATIONS
Demand-driven Automation
Intelligent Lighting
Human Centric Lighting
Light control with DALI-2

COMPANY
Vision and mission
Experience and quality
Corporate responsibility
Research and development
Cooperations and
memberships
Awards and prizes
References

PRESS
Press releases
Images
ESYWORLD

Imprint |
Privacy policy |
Privacy settings |
Whistleblowing |
General terms and
conditions |
Guarantee |
Disclaimer |
Contact
© 2024 ESYLUX GmbH

