

TECHNICAL Data

**DOWNLOADS** 

# **SPARE PARTS**



 NiCd battery (3.6 V/800 mAh) with reverse polarity protected connection for use with single-battery escape route signage from the SLX series

# **TECHNICAL DATA**

# **GENERAL**

Device category	Battery
Conformity	CE, EAC

#### HOUSING

Dimensions	Length 153 mm x Width 15 mm x Height/Depth 15 mm
Weight	650 g

Permissible ambient temperature 5 °C...+35 °C

# **ELECTRICAL VERSION**

Nominal voltage	3.6 – 3.6 V
-----------------	-------------

# **DOWNLOADS**

GENERAL		All files as ZIP	
Data sheet	PDF		<u>•</u>

## **TENDER SPECIFICATIONS**

TENDER SPECIFICATIONS		
Invitation to tender text neutral (rtf)	RTF	<u>•</u>
Invitation to tender text neutral (x81)	X81	<u>•</u>
Tender text with leading brand	RTF	<u>•</u>

# **FITTING PRODUCTS**

# **ESCAPE SIGN LIGHT**

# SLX EL LED DISPLAY 3h 24m IR SM Item number EN10077371 Single-battery emergency light for escape route signage with 3-h emergency light duration for 24-m detection range in accordance with DIN EN 1838



#### SLX EL LED DISPLAY 3h 32m IR SM

Item number EN10077210

Single-battery emergency light for escape route signage with 3 h emergency light duration for 32 m detection range in accordance with DIN EN 1838









## SLX EL LED DISPLAY 8h 24m IR SM

Item number EN10077388

Single-battery emergency light for escape route signage with 8-h emergency light duration for 24-m detection range in accordance with DIN EN 1838











#### SLX EL LED DISPLAY 8h 32m IR SM

Item number EN10077319

Single-battery emergency light for escape route signage with 8 h emergency light duration for 32 m detection range in accordance with DIN EN 1838











#### SLX EL LED FLAT COVER 3h 14m IR WM

Item number EN10077609

Single-battery emergency light for escape route signage with 3 h emergency light duration for 14 m detection range in accordance with DIN EN 1838











#### SLX EL LED FLAT COVER 3h 24m IR WM

Item number EN10077241

Single-battery emergency light for escape route signage with 3-h emergency light duration for 24-m detection range in accordance with DIN EN 1838











## SLX EL LED FLAT COVER 8h 14m IR WM

Item number EN10077616

Single-battery emergency light for escape route signage with 8 h emergency light duration for 14 m detection range in accordance with DIN EN 1838











#### SLX EL LED FLAT COVER 8h 24m IR WM

Item number EN10077302

Single-battery emergency light for escape route signage with 8-h emergency light duration and viewing distances of 24 m in accordance with DIN EN 1838









## SLX EL LED HIGH COVER 3h 24m IR SM

Item number EN10077357

Single-battery emergency light for escape route signage with 3-h emergency light duration for 24-m detection range in accordance with DIN EN 1838











#### SLX EL LED HIGH COVER 3h 32m IR SM

Item number EN10077203

Single-battery emergency light for escape route signage with 3 h emergency light duration for 32 m detection range in accordance with DIN EN 1838











#### SLX EL LED HIGH COVER 8h 24m IR SM

Item number EN10077364

Single-battery emergency light for escape route signage with 8-h emergency light duration for 24-m detection range in accordance with DIN EN 1838











#### SLX EL LED HIGH COVER 8h 32m IR SM

Item number EN10077326

Single-battery emergency light for escape route signage with 8 h emergency light duration for 32 m detection range in accordance with DIN EN 1838













#### **SERVICE**

#### **Downloads**

Catalogues and brochures

Videos

Tender specifications

KNX product database

Mobile apps

#### Knowledge

Academy & Training

Name concept

Online Demo ESY-App

Covers for wall detectors

**Ecodesign Directive** 

**Presence and Motion detectors** 

# Support

Planning & project support

BIM-Portal

#### **ESYLUX Services**

ESYCOMPARE

ESYWORLD

#### **SOLUTIONS**

#### Offices

Group offices

Open-plan office

Meeting rooms

Reversible offices

Communal areas

# Education

Classrooms

Break rooms

Mensas

#### **Daycare centers**

Playrooms

#### **Health Care**

Patient rooms

**Examination rooms** 

Multi-purpose rooms

Canteens

#### **Outdoor areas**

Pathways and entrances

Multi-storey car parks

Outdoor car parks

#### Secondary areas

Corridors

Staircases

Side rooms

Sanitary facilities

#### **PRODUCTS**

#### Indoor automation

Presence and motion detectors

 $Brightness\ controller$ 

Controls

Cmaka alarm

#### **Indoor lighting**

Lighting systems

Recessed lights

Wall and ceiling lights

Downlights

Moisture-proof lights

**Emergency lights** 

Portable spotlight

#### **Outdoor automation**

Motion detectors

Twilight switch

#### **Outdoor lighting**

Wall lights

Up-/Downlights

**Bollard lights** 

Floodlights

#### HIGHLIGHTS

ALVA

SVENJA

**Emergency Lights** 

CELINE-2

SLP-2

ATMO

Downlights

Outdoor Floodlights

ESYLUX Light Control

DEFENSOR

COMPACT

ESY-Pen

FLAT

OLIVIA-2

Switch lights on and off

hygienically

Focus products Q2/2024

#### **INNOVATIONS**

Demand-driven Automation Intelligent Lighting Human Centric Lighting Light control with DALI-2

#### **COMPANY**

Vision and mission Experience and quality Corporate responsibility Research and development

Cooperations and memberships

Awards and prizes

References

#### **PRESS**

Press releases

Images

ESYWORLD

Imprint
Privacy policy
Privacy settings
Whistleblowing
General terms and
conditions
Guarantee
Disclaimer
Contact
© 2024 ESYLUX GmbH











