

Powersource

6~20kVA Single phase Tower UPS



Power range

6~20kVA



Operation

1P/1P, online double conversion



Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



Characteristics

- Intelligent battery management.
- 3-level topology, high performance and efficiency.
- Online double conversion, full digital control.
- Output PF=1, high load adaptability.
- Wide range of input voltage tolerance.
- Adapt to half-wave load.
- Auto fault waveform recording.
- Self-aging function to save test energy

Model	SS006B	SS006L	SS010B	SS010L	SS015L	SS020L
Rate Power	6kVA/6kW	6kVA/6kW	10kVA/10kW	10kVA/10kW	15kVA/15kW	20kVA/20kW
Cold start	Default output 50/60Hz					
Input voltage range	110~288VAC (220/230/240VAC); 176VAC~288VAC,full load;176~110 VAC ,power derate from 100% to 50%					
Input power factor	≥0.99					
Frequency range	40-70Hz					
Output frequency	50/60Hz, self adaption					
Output power factor	1					
Rate output	220/230/240VAC					
Load regulation	±1%					
Output THDu	≤1%THD, linear load; ≤5%THD, non-linear load					
Transfer time-main to BAT	0ms					
Transfer time-INV to BYP	0ms					
Efficiency-normal mode	Max 95%					
Efficiency-ECO mode	98%					
Noise (1 meter)	58dB				62dB	
Overload (normal mode)	110%:10mins;125%:1min;150%: 30 seconds					
Battery	Model	12VDC/7Ah	External, 16-24 settable	12VDC/9Ah	External, 16-24 settable	External, 16-24 settable
	Quantity	16		16		
	Max charging	1A	5A	1A	5A	5A
	Rate voltage	Default 192VDC, settable				
Crest	3:1					
Display	LED+LCD					
Standard	RS232, EPO, RS485					
Option	AS400, SNMP card, Parallel kit, Maintenance bypass kit, 12A charger, Air filter					
Dimension, W*D*H (mm)	190*605*705	190*605*338	190*605*705	190*605*338	190*564*550	
Weight (kg)	56	14	60	16	30	

Statement: The products will continue to be innovative and optimized, which may lead to asynchronized updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.