

## AMAXX-kontaktkombinasjon

Bestillingsnr. 957148




- Kablet og klart til bruk
- Sidehengslet hus
- Hus og boksinnsett av AMAPLAST
- Sikring under transparent betjeningsklaff

## Tekniske spesifikasjoner

|                           |                                                                                                                                                                                                                                                               |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CEE 63 A, 5 p, 400 V      | 1                                                                                                                                                                                                                                                             |
| CEE 32 A, 5 p, 400 V      | 1                                                                                                                                                                                                                                                             |
| CEE 16 A, 5 p, 400 V      | 1                                                                                                                                                                                                                                                             |
| SCHUKO®                   | 2                                                                                                                                                                                                                                                             |
| Fusing                    | <ul style="list-style-type: none"> <li>• 1 Jordfeilautomat 32A 4p C 6kA</li> <li>• 1 Jordfeilautomat 16A 4p C 6kA</li> <li>• 1 Jordfeilautomat 16A 2p C 10kA</li> <li>• 1 Jordfeilautomat 16A 2p C 10kA</li> <li>• 1 Jordfeilautomat 16A 2p C 10kA</li> </ul> |
| Forankoblet sikring maks. | 63 A                                                                                                                                                                                                                                                          |
| InA                       | 57 A                                                                                                                                                                                                                                                          |
| RDF                       | 0.4                                                                                                                                                                                                                                                           |
| Connection / feeder cable | • for 2 kabler opptil 5 x 25 mm <sup>2</sup> (fleksibel maks. 16 mm <sup>2</sup> )                                                                                                                                                                            |
| Kapslingsgrad             | IP44                                                                                                                                                                                                                                                          |
| Berøringsbeskyttelse      | false                                                                                                                                                                                                                                                         |
| Husmateriale              | kunststoff                                                                                                                                                                                                                                                    |
| Vekt                      | 8500 g                                                                                                                                                                                                                                                        |

## Dimensjoner



Drawing 1 MB 540

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 186 mm |
|                    | IP 67   | 208 mm |
| CEE 16A, 3p, 230V  | IP 44   | 216 mm |
|                    | IP 67   | 220 mm |
| CEE 16A, 5p, 400V  | IP 44   | 222 mm |
|                    | IP 67   | 226 mm |
| CEE 32A, 5p, 400V  | IP 44   | 231 mm |
|                    | IP 67   | 236 mm |
| CEE 63A, 5p, 400V  | IP 44   | 260 mm |
|                    | IP 67   | 260 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.