




DECLARATION OF PERFORMANCE  
No. 534525

1. Unique identification code of the product-type: **X-TACK**
2. Intended use/es:  
**Sealant for façade, exterior and interior, in Cold Climate (F EXT-INT CC 12.5 E)**  
**Sealant for sanitary joints (S XS3)**  
**Sealant for pedestrian walkways, exterior and interior, in Cold Climate (PW EXT-INT CC 12.5 E)**
3. Manufacturer: **Novatech International NV**  
**Industrielaan 5b**  
**2250 Olen - Belgium**
4. System of AVCP: **3 plus 3**
5. Harmonised standard:  
**EN 15651-1: 2012-12**  
**EN 15651-3: 2012-12**  
**EN 15651-4: 2012-12**
6. Notified body: **NB 0757 - IFT Rosenheim**





7. Declared Performance(s)

Conditioning: Method B

Substrate: anodized aluminum (with PPE Primer) and concrete M1 (with primer SIP 1K)

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012-12 EN 15651-3: 2012-12 EN 15651-4: 2012-12
Release of chemicals dangerous to the environment and health	See SDS	
Water tightness and air tightness		
Resistance to flow	≤ 3mm	
Loss of volume	≤ 10%	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Tensile properties (secant modulus / elongation at break)	NF	
Tensile properties (secant modulus) at -30°C	NF	
Adhesion/cohesion properties at maintained extension after water immersion	NF	
Adhesion/cohesion properties at maintained extension after saltwater immersion	NF	
Microbiological growth	3	
Tear resistance	NF	
Durability	Pass	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Dr. Gunther Dreezen

Director of R&D  
Olen, 20 August 2021

