


Heat shrinkable tubing set 3:1 (40/13), several colours, pre-cut pieces 10x25 cm

Art.-No. 308-34010 | HIS-3-BAG-40/13-PO-X-MIX | 



- Thin wall and flexible tubing made of cross-linked Polyolefin
- High shrink ratio 3:1
- Handy, small packaging with 10 pre-cut pieces of 250 mm
- Fits highly variable cable diameters



More products in this product group:
[Heat shrinkable tubing 3:1 in blister bags >](#)

Base Data

Application	HIS-3 BAG tubings are useable for insulation and protection of cables and connectors
Behaviour At Low Temperature	not cracking
Behaviour at Heat Shock	not fluid, not dripping, not cracking
Behaviour at low Temperature test method	UL 224
Colour	Various (MIX)
Elongation At Heat Aging	400 %
Heat Aging Test	168h/175°C
Heat Aging test method	UL 224
Heat Shock Test	4h/250°C
Material	Polyolefin, cross-linked (PO-X)
Minimum Tensile Strength At Heat Aging	13 MPa
PART DESCRIPTION	HIS-3-BAG-40/13-PO-X-MIX
Pack Cont.	10 pcs.
Package Content packed in	bag
Printable	No
Product Family	HIS-3 BAG
Product Group	Heat shrinkable tubing 3:1 in blister bags
Short Description	Heat shrinkable tubing set 3:1 (40/13), several colours, pre-cut pieces 10x25 cm
Shrink Ratio	3:1
Type	HIS-3-BAG-40/13
Variant	Thin-Wall
With inner glue (Yes/No)	No



Length (L)	250 mm
Longitudinal Change After Shrinkage	+/-5%
Recov. \varnothing d max.	13 mm
Supplied \varnothing D min.	39 mm
Wall (WT)	1.25 mm
Weight/Unit	0.017 kg

Specifications

Dielectric Strength	32 kV/mm
Dielectric Strength test method	IEC 60243
ELV compliant (Article 4 - 2)	YES
Elongation at break	800
Elongation at break test method	ASTM D2671
Flammability	UL 224 VW-1
Hazardous Goods	No
Insulation Class	B (VDE 0530)
Min. Shrink Temperature - °C	+100 °C
Operating Temperature	-55 °C to +135 °C
ROHS compliant	Yes
Self extinguishing	Yes
Specifications	ANSI/UL 224
Specifications	
Tensile Strength	14 MPa
Test Method Tensile Strength	ASTM D2671
UL Listed (US and Canada)	No
UL OCD link	Link Link
UL Recognized (US and Canada)	Yes
UL-File Number	E143529
Volume Resistance	$10^{14} \Omega$ cm
Volume Resistance test method	UL 224
Water Absorption	0.15 %



Country of Origin	CN
Customs Number	39173200
GTIN-13 / EAN	4031026401287
Packaging 1 - Height (m)	0.032 m
Packaging 1 - Length (m)	0.335 m
Packaging 1 - Qty	10
Packaging 1 - Type	bag
Packaging 1 - Volume (m ³)	0.00107 m ³
Packaging 1 - Weight (kg)	0.170001 kg
Packaging 1 - Width (m)	0.1 m

More Information

ETIM 7.0 Key	EC000217
ETIM 8.0 Key	EC000217
ETIM 9.0 Key	EC000217
UNSPSC Key	39121723