

Specifications



Eaton EP-401371

Eaton Touch panel XV-313, 24 V DC, 7 Inch, 1 x Ethernet, 1 x RS-232, 1 x RS-485, 1 x CAN, Linux, Capacitive multi touch, PLC

General specifications

PRODUCT NAME	Eaton XV-313 Touch panel
CATALOG NUMBER	EP-401371
MODEL CODE	XV-313-70-B00-A00-2C
EAN	7640130100251
PRODUCT LENGTH/DEPTH	209 mm
PRODUCT HEIGHT	55.7 mm
PRODUCT WIDTH	151 mm
PRODUCT WEIGHT	0.8 kg

CERTIFICATIONS	CUL UL File No.: E205091 Certified by UL for use in Canada UL 61010-2-201 CE UL IEC/EN 61000-6-2 IEC/EN 61000-6-4 DNV DNV TAA00000NC
-----------------------	--



Powering Business Worldwide

Features & Functions

ENCLOSURE MATERIAL	Insulated material
FITTED WITH:	Message system (incl. buffer and confirmation) Recipes SW interfaces Color display Printer output 1 x RS485 (built-in interface) 1 x Ethernet 10/100 Mbps (built-in interfaces) Message indication 1 x RS232 (built-in interface) 1 x USB host 2.0 (built-in interface) 1 x CAN (built-in interfaces)
FUNCTIONS	Process default value (input) possible Process value representation (output) possible Additional software components, loadable

Ambient conditions, mechanical

SHOCK RESISTANCE	15 g, 11 ms, Mechanical
VIBRATION RESISTANCE	5 - 9 Hz, ± 3.5 mm 60 - 150 Hz, ± 2 g 9 - 60 Hz, ± 0.15 mm

General

BATTERY RUNTIME	Back-up of real-time clock: BR 2330, non-replaceable (soldered)
DEGREE OF PROTECTION	NEMA 4X NEMA 12 IP20, rear (according to EN 60529-1)
DEGREE OF PROTECTION (FRONT SIDE)	NEMA 12 IP65
FUSE TYPE	Built-in fuse (not accessible)
LIFESPAN	50,000 h (Service life of back-lighting)
MODEL	Plastic enclosure and glass panel in aluminum mounting frame
MOUNTING METHOD	Flush mounting - Clearance: Width x Height x Depth ≥ 30 mm (1.18") Rear mounting Flush mounting - Inclination from vertical: $\pm 45^\circ$ (if using natural convection)
POTENTIAL ISOLATION	Power supply: no
PROTECTION AGAINST POLARITY REVERSAL	Yes
PRODUCT CATEGORY	XV-300
ROHS CONFORMITY	Yes
SOFTWARE	GALILEO, Visualization software, Engineering XSOFT-CODESYS-3, PLC-Programming software, Engineering XSOFT-CODESYS-3, Visualization software, Engineering
TYPE	Control panel with PLC for rear mounting
VOLTAGE TYPE	DC
CLIMATIC ENVIRONMENTAL CONDITIONS	
AIR PRESSURE	795 - 1080 hPa (operation)
AMBIENT OPERATING TEMPERATURE - MIN	0 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT STORAGE TEMPERATURE - MIN	-20 °C
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-3 Cold to EN 60068-2-1 Dry heat to IEC 60068-2-2

ENVIRONMENTAL CONDITIONS	Condensation: Non-condensing
OPERATING TEMPERATURE - MIN	0 °C
OPERATING TEMPERATURE - MAX	50 °C
RELATIVE HUMIDITY	10 - 95 % (non-condensing)

Electro magnetic compatibility

EMITTED INTERFERENCE	According to IEC/EN 61000-6-4
INTERFERENCE IMMUNITY	According to EN 61000-6-2
VOLTAGE DIPS	≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC)

Electrical rating

PERMISSIBLE VOLTAGE	19.2 - 30 V DC, effective (rated operating voltage -20 %/+25 %) 18 - 31.2 V DC, battery powered (rated operating voltage -25 %/+30 %) 35 V DC (for a duration of < 100 ms) 18.0 - 31.2 V DC, absolute with ripple
POWER CONSUMPTION	11.9 W Max. 14.4 W 14 W typ.
RATED OPERATIONAL VOLTAGE	24 V DC (power-supply - safety extra low voltage)
SUPPLY VOLTAGE AT AC, 50 HZ - MIN	0 VAC
SUPPLY VOLTAGE AT AC, 50 HZ - MAX	0 VAC
SUPPLY VOLTAGE AT DC - MIN	19.2 VDC
SUPPLY VOLTAGE AT DC - MAX	30 VDC

Communication

INTERFACES	USB 2.0 host (not galvanically isolated) 10/100 Mbps Ethernet connection RS485 (not galvanically isolated, 9-pin SUB-D plug, UNC) CAN (not galvanically isolated, 9-pin SUB-D plug, UNC) RS232 (not galvanically isolated, 9-pin SUB-D plug, UNC)
NUMBER OF SLOTS	1 (for SD-Card)
PROTOCOL	EtherCAT CAN MODBUS TCP/IP EtherNet/IP

Display

DISPLAY CONTRAST RATIO	850:1
DISPLAY LIGHTING	LED Dimmable via software
DISPLAY SIZE	16:9 153.6 x 90.0 mm
DISPLAY TYPE	TFT Color display, TFT, anti-glare Anti-glare tempered glass in plastic bezel
LUMINANCE INTENSITY	400 cd/m ²
NUMBER OF COLORS OF THE DISPLAY	16777216
RESOLUTION	<ul style="list-style-type: none"> 1024 x 600 px WSVGA
SCREEN SIZE (DIAGONAL)	7 in

System	
BACKUP TIME	10 years, typ. (time at zero voltage)
MEMORY	NVRAM: 128kByte Retain DRAM: 512 MByte RAM Flash: 1 GByte SLC SD card, Type: SDSC, SDHC (external memory)
MEMORY CAPACITY	512,000 kByte
OPERATING SYSTEM	Linux
PROCESSOR	ARM Cortex-A9 800 MHz

TOUCH TECHNOLOGY	Multi-touch touch panel touch sensor Projected Capacitive Touch (PCT) Capacitive multitouch
-------------------------	---

Design verification	
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	14.4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	14.4 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Meets the product standard's requirements.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES	eaton-xv-303-xv313-hmi-plc-brochure-br050003-en-us
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf eaton-hmi-plc-touch-panel-xv-363-flyer-fl048001en-en-us.pdf
DECLARATIONS OF CONFORMITY	DA-DC-00005047.pdf DA-DC-00005053.pdf
INSTALLATION INSTRUCTIONS	eaton-hmi-xv-313-il048023zu.pdf
MANUALS AND USER GUIDES	eaton-systemdescription-with-embedded-linux-mn050017en-us.pdf eaton-hmi-xv300-multi-touchdisplay-manual-mn048031en-us.pdf
MCAD MODEL	eaton-cadenas-front_view-179671_front.pra eaton-cadenas-side_view-179671_side.pra eaton-cadenas-top_view-179671_top.pra

	eaton-xv_313_70_b00_a00_xc-3d-model.stp eaton-xv_313_70_b00_a00_xc-drawing.dwg eaton-cadenas-path-panels-xv_300-179671.3db
MULTIMEDIA	System solutions based on EtherCAT
PRODUCT NOTIFICATIONS	eaton-xv303-xv313-end-user-license-agreement-mz048008-en-us.pdf eaton-xv303-xv313-product-cybersecurity-guideline-mz048009-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

