

FDV - Merkeskiltholder, WEF 1 BS/35

EFA-varenr.:	121000883
EI-nummer:	1273881
Leverandørens varenr.	69.920.1053.0
Type betegnelse:	WEF 1 BS/35
GTIN-nr.:	4015573648388
Leverandør:	Wieland Electric GmbH
Sertifikat:	
Etim-klasse:	EC001041 - Endebrakett for rekkeklemme
Tolltariff:	85389000
Salgsenhet:	Stk
Blokk nr.:	100103



Beskrivelse

Merkeskiltholder WEF

Teknisk beskrivelse

Material:

Polyamide 66/6 black figures on white background DIN rail terminal blocks, type WKF, can accept marking tags on both sides on top of the block in a 3-chamber slot. It can be either 3 single number tags from the tear-off marking strip, or single tags, or marking strips.

1. Marking strips marked and unmarked, made from Polyamide 66/6, suitable for 10 blocks in a row.

BZ WKF1.5 block center (4 mm spacing)

BZ WKF1.5/10 outer side of block (4 mm spacing) for DIN rail terminal blocks of type WKF 1.5 ,

9705 A/5/10 (5 mm spacing) for DIN rail terminal blocks of type WKF 2.5 ,

9705 A/6/10 (6 mm spacing) for DIN rail terminal blocks of type WKF 4 ,

9705 A/8/10 (8 mm spacing) for DIN rail terminal blocks of type WKF 6 ,

9705 A/5/10/5 (10 mm spacing) for DIN rail terminal blocks of type WKF 10 ,

9705 A/6/10/5 (12 mm spacing) for DIN rail terminal blocks of type WKF 16 ,

9705 A/8/10/5 (16 mm spacing) for DIN rail terminal blocks of type WKF 35 ,

2. Tear-off marking strip with 10 marking tags, made from Polyamide 66/6, white, marked and unmarked.

This marking system considerably reduces the time required for marking terminal block assemblies. For numerical marking of terminal block rows only 11 stock positions are required. As the time used for picking and attaching the tags is reduced, and as stockkeeping is low and the prices extremely favorable, attractive cost savings are the result from using these tear-off marking strips. Type 9704 A... (see page 219)

3. Single marking tag made from white Polyamide 66/6, marked and unmarked. Type 9705 A

ETIM-egenskaper

Farge	Svart
Monteringsmetode	DIN-skinne, 35 mm
Forriglingsform	Skrueløs



Materiale	Plast
Materialkvalitet	Andre
Isolasjonmaterialets flammehemmend	V2
Bredde	8
Dybde	52

Retur/Deponi

Produktet skal leveres til godkjent avfallsdeponi.