

Airam Led

4W 15000h BX

Dimmable range for all residential lighting needs

A lamp series covering all residential lighting needs. All models are dimmable with an LED dimmer. The clear DIM symbol indicates dimmability. The lamps have a pleasant warm white (2700 K) colour temperature. The opal light source provides non-glaring light. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented. Ensure the compatibility of the range's 12V lamps with your transformer.

Clear dimmable R50 reflector LED lamp 4W 4000K
E14 345lm 36D 15000h 50x84mm, cardboard packing.
Supply frequency ~50/60Hz.



4W 15000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714125	A7LEF1	0.053	Airam Led

4W 15000h BX

EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	Transparent
Housing colour	Colourless

Dimming and control

Dimming phase cut-on	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	345
Luminous flux (max) (lm)	345
Luminous intensity (cd)	570
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min)	36
Beam angle (max)	36
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Diameter (mm)	50
Length (mm)	84

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	20
Nominal current (max) (mA)	24
Power factor	0.8
Voltage type	AC