

LITELINE IP66+



Liteline IP66+ is a luminaire for demanding environments, designed to withstand corrosive conditions and suitable for areas such as pigsties, cow sheds, and stables. The well-considered design allows connection and driver access without opening the diffuser. Control the lighting via On/Off or DALI. The sliding brackets make installation quick and smooth. With Liteline IP66+, you get replaceable LED and driver, the option to choose colour temperature 3000K/4000K, and adjust the luminous flux via DIP-switch. Through-wiring On/Off 5x2.5 mm². M20 cable gland in each end cap and an optional accessory with 2x M20 cable glands if needed. Suitable for trunking rail mounting, keyholes for ceiling mounting, and integrated wire suspension with hook and hook lock. D-marked for protection against increased fire risk.

- Fluorescent replacement ideal for corrosive environments such as livestock buildings
- Replaceable LED and driver
- D-marked according to SS-EN 60598-2-24 – for areas with increased fire risk
- Mounting options: trunking rail, surface ceiling, wall or wire
- Control the lighting via On/Off or DALI
- Lifetime L80 100,000h Ta 25°C
- Lifetime driver 100,000h /10%



LITELINE IP66+



GTIN

7392971150642 1500
7392971150659 1500 DALI

Type

1500
1500 DALI

Color Temperature

3000K/4000K
3000K/4000K

Luminaire lumen

5500-8550lm
5400-8400lm

Beam angle

105°
105°

Effect luminaire

36-55W
34-52W

