



Backlit Panel,6060,32W, 3000/3500/4000 K,3840lm, UGR19,W/O Driver

Backlit Panel,6060,32W,3000/3500/4000K,3840lm,UGR19,
W/O Driver

ID: 0028920225

GTIN: 7630268419127

5 YEARS *
WARRANTY



Technical Data

Rated luminous flux according to IEC 62722-2-1:	3840 lm
Luminaire efficacy:	120 lm/W
Colour temperature:	3000...4000 K
Colour rendering index CRI:	80-89
McAdam step/SDCM(self-define center):	3
Unified Glare Ratio (UGR):	19
Beam angle:	Extreme wide beam >80°
Light distributor:	Diffuser lens/optic/panel
Energy efficiency class of the light source according to EU regulation 2019/2015:	D
Protection class:	III
Nominal voltage:	32...40 V
Frequency(Hz):	50/60
Nominal current:	850...850 mA
Max. system power	32
Power factor:	0.9
Max.number of luminaires per miniature circuit breaker B10(MCB)	NA
Max.number of luminaires per miniature circuit breaker C10(MCB)	NA
Max.number of luminaires per miniature circuit breaker B16(MCB)	NA
Max.number of luminaires per miniature circuit breaker C16(MCB)	NA
Connection type	Push-in
Plug type	NA
Rated life time L70/B50 at 25 °C:	100000 h
Rated life time L80/B10 at 25 °C:	50000 h
Impact strength:	IK02
Degree of protection (IP):	IP20
Rated ambient temperature according to IEC 62722-2-1:	-20...40 °C
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Photobiological safety according to EN 62471:	RG0
Covering of the luminaire with thermally insulating material possible:	Yes
Housing material:	Aluminium
Housing colour:	White
Length:	595 mm
Width:	595 mm
Height/depth:	32 mm



Additional Information

Driver included	No
Type of LED driver:	NA
Number of driver:	NA
Mounting method:	ceiling mounting Built-in mounting
Cable connection details(qty, diameter, etc.):	NA
LMS Protocol (when it's DALI):	NA
Number of DALI address (when it's DALI):	NA
Certification/Norms:	CE/REACH/RoHS/ERP
Net weight(kg)	1.51
Gross weight with packaging(kg):	2.04
Accessories included in the packaging:	NA

