

Backlit Panel

Backlit Panel, 30120,32W ,30/35/40K,3840lm,UGR19,W/O Driver

Model No.:



SGSO Sku:

0028920226

GTIN/EAN:

7630268419134

Suitable for ceiling mounting:	Yes
Suitable for built-in mounting:	Yes
Suitable for workplace according to EN 12464-1:	Yes
Lamp type:	LED not exchangeable
Housing material:	Aluminium
Surface protection housing:	Powder coating
Housing colour:	White
Material cover:	Plastic, structured
Voltage type:	DC
Nominal voltage:	32 ... 40 V
Nominal current:	850 mA
Type of control gear:	LED operating device current-controlled
No dim function:	Yes
Light sharing:	Symmetric
Beam angle:	Extreme wide beam >80°
Colour consistency (McAdam ellipse):	SDCM5
Light outlet:	Indirect
Energy efficiency class of the light source according to EU regulation 2019/2015:	E
Rated life time L70/B50 at 25 °C:	100000 h
Degree of protection (IP):	IP20
Degree of protection (NEMA):	Other
Impact strength:	IK02
Protection class:	III
Rated ambient temperature according to IEC 62722-2-1:	-20 ... 40 °C
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Suitable for lamp power:	32 W
Max. system power:	35.2 W
Luminaire efficacy:	120 lm/W
Rated luminous flux according to IEC 62722-2-1:	3840 lm
Colour of light:	White
Colour temperature:	3000 ... 4000 K
Flickering value Pst LM:	1
Colour rendering index CRI:	80-89
Power factor:	0.9
Stroboscope effect value SVM:	0.4
Width:	295 mm
Height/depth:	32 mm
Length:	1195 mm
Type of wiring:	Ending
Conductor cross section:	0.5 mm ²
Connection type:	Push-in clamp
Total harmonic distortion:	0.2
Photobiological safety according to EN 62471:	RG0
Unified Glare Ratio (UGR):	19
Colour of light adjustable:	Positions
LED-Panel:	Yes



On/Off Driver + Connection Box included



Safety Cable included

