



Driver 32 ,On/off+3Power Slide Switch, CII,White, 100 000H, W/O Box,W/2M HFFR cable+EU Plug

Driver 32 ,On/off+3Power Slide Switch, CII,White, 100 000H, W/O Box,W/2M HFFR cable+EU Plug



ID: 0027100051

GTIN: 7630268417543

5 YEARS * WARRANTY

Technical Data	
Model:	Static
No dim function:	yes
Housing:	Plastic housing
Suitable for constant current:	yes
Suitable for constant voltage:	no
Output voltage:	32...40 V
Output current:	700...850 mA
Suitable for DC-voltage (primary side):	no
Output power:	22.4...34 W
Power consumption:	32 W
Degree of protection (IP):	IP20
Protection class:	II
Length:	171 mm
Width:	39 mm
Height:	25 mm



Additional Information	
Power factor	>0.9@Full load
Temperature range	-20...+40° C
Cable connection	Push terminal
Cable length(input/output)	2.0/0.15M
Cable cross-section(input/output)	0.5...1.5mm²/0.5...1.5mm²
Inrush current	8.7A
Surge capability(L/N-G)	2 KV
Surge capability(L-N)	1KV
Certification/Norms	CE/REACH/RoHS/ERP
SELV	Yes
Overheating protection	Yes
Overload protection	Yes
No-load protection	Yes
Short-circuit protection	Yes
Product weight	189g
Product weight with packaging	221g
Compatible panel	Malta/Malta+/Palma+
Linkable Qty B16	NA
Linkable Qty C16	NA
Linkable Qty B10	NA
Linkable Qty C10	NA
Covering with thermal insulating material or not	NA

