

# Specifications



Photo is representative



## Eaton 191587

Eaton Moeller series NZM - Molded Case Circuit Breaker. NZM3 PXR10 circuit breaker, 630A, 3p, box terminal

### General specifications

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM molded case circuit breaker electronic |
| <b>CATALOG NUMBER</b>       | 191587                                                          |
| <b>MODEL CODE</b>           | NZMN3-AX630-BT                                                  |
| <b>EAN</b>                  | 4015081920990                                                   |
| <b>PRODUCT LENGTH/DEPTH</b> | 166 mm                                                          |
| <b>PRODUCT HEIGHT</b>       | 275 mm                                                          |
| <b>PRODUCT WIDTH</b>        | 140 mm                                                          |
| <b>PRODUCT WEIGHT</b>       | 7.68 kg                                                         |
| <b>COMPLIANCES</b>          | RoHS conform                                                    |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC                                             |
| <b>GLOBAL CATALOG</b>       | 191587                                                          |

## Product specifications

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>AMPERAGE RATING</b>                                                                  | 630 A                                                                                                                            |
| <b>VOLTAGE RATING</b>                                                                   | 690 V - 690 V                                                                                                                    |
| <b>CIRCUIT BREAKER FRAME TYPE</b>                                                       | NZM3                                                                                                                             |
| <b>FEATURES</b>                                                                         | Motor drive optional<br>Protection unit                                                                                          |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                                                                                       |

## Resources

|                                  |                                                                                                                                                                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                 | <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a><br><a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a>                                                                                                                                                            |
| <b>CATALOGS</b>                  | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-029.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-015.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-011.eps</a> |
| <b>CHARACTERISTIC CURVE</b>      | <a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250293en.pdf</a>                                                                                                                                                                                                                  |
| <b>DRAWINGS</b>                  | <a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-016.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-020.eps</a>                                                                                                                                                               |
| <b>INSTALLATION INSTRUCTIONS</b> | <a href="#">eaton-circuit-breaker-basic-unit-bg3-il012100zu.pdf</a>                                                                                                                                                                                                                                         |
| <b>INSTALLATION VIDEOS</b>       | <a href="#">The new digital NZM Range</a><br><a href="#">Introduction of the new digital circuit breaker NZM</a>                                                                                                                                                                                            |
| <b>MCAD MODEL</b>                | <a href="#">DA-CD-nzm3_3p</a><br><a href="#">DA-CS-nzm3_3p</a>                                                                                                                                                                                                                                              |
| <b>TECHNICAL DATA SHEETS</b>     | <a href="#">eaton-nzm-technical-information-sheet</a>                                                                                                                                                                                                                                                       |

|                                                                 |                                                                                                      |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                                           |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                                               |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                                               |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                                               |
| <b>POLLUTION DEGREE</b>                                         | 3                                                                                                    |
| <b>MOUNTING METHOD</b>                                          | Built-in device fixed built-in technique<br>Fixed                                                    |
| <b>CLIMATIC PROOFING</b>                                        | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                       |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 119.07 W                                                                                             |
| <b>UTILIZATION CATEGORY</b>                                     | A (IEC/EN 60947-2)                                                                                   |
| <b>ISOLATION</b>                                                | 500 V AC (between auxiliary contacts and main contacts)<br>300 V AC (between the auxiliary contacts) |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 70 °C                                                                                                |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                      | -25 °C                                                                                               |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                        | 70 °C                                                                                                |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                        | 40 °C                                                                                                |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>      | 0                                                                                                    |

|                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                       | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110                                                                                                                                                                                                                                                                                                                                                                          |
| <b>DEGREE OF PROTECTION</b>                                    | IP20 (basic degree of protection, in the operating controls area)<br>IP20                                                                                                                                                                                                                                                                                                                                                                |
| <b>DIRECTION OF INCOMING SUPPLY</b>                            | As required                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>              | Frame clamp                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>LIFESPAN, MECHANICAL</b>                                    | 15000 operations                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>                   | IP40 (with insulating surround)<br>IP66 (with door coupling rotary handle)                                                                                                                                                                                                                                                                                                                                                               |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>                     | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)                                                                                                                                                                                                                                                                                                                                                         |
| <b>NUMBER OF POLES</b>                                         | Three-pole                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>                        | <p>10 segments of 50 mm x 1 mm (2x) at rear-side width extension<br/> Max. 8 segments of 24 mm x 1 mm (2x) at box terminal<br/> Min. 6 segments of 16 mm x 0.8 mm at box terminal<br/> Max. 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm at rear-side connection (punched)</p> <p>Max. 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm<br/> Min. 6 segments of 16 mm x 0.8 mm at rear-side connection (punched)</p> |
| <b>LIFESPAN, ELECTRICAL</b>                                    | 3000 operations at 690 V AC-1<br>5000 operations at 415 V AC-1<br>5000 operations at 400 V AC-1                                                                                                                                                                                                                                                                                                                                          |

|                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FUNCTIONS</b>                                                     | System and cable protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>TYPE</b>                                                          | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>SPECIAL FEATURES</b>                                              | <ul style="list-style-type: none"> <li>• Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity <math>I_{cn}</math>)</li> <li>• Overload and short-circuit protection LI</li> <li>• R.m.s. value measurement and "thermal memory"</li> <li>• USB interface for configuration and test function with Power Xpert Protection Manager software</li> <li>• Rated current = rated uninterrupted current: 630 A</li> <li>• Terminal capacity hint: Up to 240 mm<sup>2</sup> can be connected depending on the cable manufacturer.</li> </ul> |
| <b>APPLICATION</b>                                                   | Use in unearthed supply systems at 690 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>SHOCK RESISTANCE</b>                                              | 20 g (half-sinusoidal shock 20 ms)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>               | Front side                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 630 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>RELEASE SYSTEM</b>                                                | Electronic release                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>SHORT-CIRCUIT TOTAL BREAKTIME</b>                                 | < 10 ms                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)</b>                | 3.3 kA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

|                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RATED SHORT-TIME<br/>WITHSTAND CURRENT (T<br/>= 1 S)</b>          | 3.3 kA                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MAX</b>       | 5040 A                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MIN</b>       | 1260 A                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>TERMINAL CAPACITY<br/>(CONTROL CABLE)</b>                         | 0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)<br>0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)                                                                                                                                                                                                                                                                                                           |
| <b>TERMINAL CAPACITY<br/>(COPPER BUSBAR)</b>                         | Min. 20 mm x 5 mm direct<br>at switch rear-side<br>connection<br>Max. 30 mm x 10 mm + 30<br>mm x 5 mm direct at<br>switch rear-side<br>connection<br>M10 at rear-side screw<br>connection<br>Max. 10 mm x 50 mm (2x)<br>at rear-side width<br>extension                                                                                                                                                      |
| <b>TERMINAL CAPACITY<br/>(COPPER SOLID<br/>CONDUCTOR/CABLE)</b>      | 16 mm <sup>2</sup> (1x) at tunnel<br>terminal<br>16 mm <sup>2</sup> (2x) direct at<br>switch rear-side<br>connection<br>16 mm <sup>2</sup> (1x) direct at<br>switch rear-side<br>connection<br>300 mm <sup>2</sup> (2x) at rear-side<br>width extension<br>16 mm <sup>2</sup> (2x) at box<br>terminal                                                                                                        |
| <b>TERMINAL CAPACITY<br/>(ALUMINUM SOLID<br/>CONDUCTOR/CABLE)</b>    | 16 mm <sup>2</sup> (1x) at tunnel<br>terminal                                                                                                                                                                                                                                                                                                                                                                |
| <b>TERMINAL CAPACITY<br/>(COPPER STRANDED<br/>CONDUCTOR/CABLE)</b>   | 25 mm <sup>2</sup> - 120 mm <sup>2</sup> (2x) at<br>box terminal<br>25 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x)<br>direct at switch rear-side<br>connection<br>35 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x) at<br>box terminal<br>16 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at<br>1-hole tunnel terminal<br>25 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x)<br>direct at switch rear-side<br>connection |
| <b>TERMINAL CAPACITY<br/>(ALUMINUM STRANDED<br/>CONDUCTOR/CABLE)</b> | 50 mm <sup>2</sup> - 240 mm <sup>2</sup> (1x) at<br>2-hole tunnel terminal<br>50 mm <sup>2</sup> - 240 mm <sup>2</sup> (2x) at<br>2-hole tunnel terminal<br>25 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) at<br>tunnel terminal                                                                                                                                                                              |

|                                                                                        |                           |
|----------------------------------------------------------------------------------------|---------------------------|
| <b>HANDLE TYPE</b>                                                                     | Rocker lever              |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>                                         | 0 A                       |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MIN</b>                                         | 0 A                       |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>                                        | 800 A                     |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>                                        | 2 A                       |
| <b>NUMBER OF OPERATIONS PER HOUR - MAX</b>                                             | 60                        |
| <b>OVERLOAD CURRENT SETTING (IR) - MAX</b>                                             | 630 A                     |
| <b>OVERLOAD CURRENT SETTING (IR) - MIN</b>                                             | 252 A                     |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ</b>     | 85 kA                     |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b> | 50 kA                     |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ</b>     | 35 kA                     |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 HZ</b>     | 13 kA                     |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 690 V, 50/60 HZ</b>     | 5 kA                      |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 400/415 V, 50/60 HZ</b>                  | 110 kA                    |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 440 V, 50/60 HZ</b>                      | 77 kA                     |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 525 V, 50/60 HZ</b>                      | 55 kA                     |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 690 V, 50/60 HZ</b>                      | 40 kA                     |
| <b>STANDARD TERMINALS</b>                                                              | Box terminal              |
| <b>OPTIONAL TERMINALS</b>                                                              | Connection on rear. Screw |

|                                                                                 |                           |
|---------------------------------------------------------------------------------|---------------------------|
|                                                                                 | terminal. Tunnel terminal |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 240 V, 50/60 HZ</b>       | 187 kA                    |
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT AUXILIARY<br/>CONTACTS</b> | 6000 V                    |
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT MAIN<br/>CONTACTS</b>      | 8000 V                    |
| <b>RATED INSULATION<br/>VOLTAGE (UI)</b>                                        | 690 V AC                  |

|                        |
|------------------------|
| <b>PROJECT NAME:</b>   |
| <b>PROJECT NUMBER:</b> |
| <b>PREPARED BY:</b>    |
| <b>DATE:</b>           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

