

Spesifikasjoner



Eaton 300360

Eaton Moeller series xEffect - FAZ MCB.
Miniature circuit breaker (MCB), 63 A, 3p,
characteristic: OV

General specifications

PRODUCT NAME	Eaton Moeller series xEffect - FAZ MCB
CATALOG NUMBER	300360
EL NUMBER	1624153
EAN	9010238117914
PRODUCT LENGTH/DEPTH	72.6 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	53.1 mm
PRODUCT WEIGHT	0.369 kg
COMPLIANCES	RoHS conform
MODEL CODE	FAZ-OV63/3



Powering Business Worldwide

Delivery Program

NUMBER OF POLES (TOTAL)	3
-------------------------	---

NUMBER OF POLES (PROTECTED)	3
-----------------------------	---

RELEASE CHARACTERISTIC	Other
------------------------	-------

AMPERAGE RATING	63 A
-----------------	------

Technical data - electrical

VOLTAGE TYPE	AC
--------------	----

RATED OPERATIONAL VOLTAGE (UE) - MAX	230 V
--------------------------------------	-------

RATED INSULATION VOLTAGE (UI)	440 V
-------------------------------	-------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
--	------

FREQUENCY RATING - MIN	50 Hz
------------------------	-------

FREQUENCY RATING - MAX	60 Hz
------------------------	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1) - ICN AT 230 V	10 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC/EN 60898-1)- ICN AT 400 V	10 kA
--	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V	15 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V	15 kA
---	-------

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	2
------------------	---

Technical data - mechanical

**WIDTH IN NUMBER OF
MODULAR SPACINGS** 3

BUILT-IN DEPTH 60 mm

DEGREE OF PROTECTION IP20

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MIN** 1.5 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (SOLID-CORE) -
MAX** 35 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MIN** 2 mm²

**CONNECTABLE
CONDUCTOR CROSS
SECTION (MULTI-WIRED)
- MAX** 16 mm²

Design verification as per IEC/EN 61439 - technical data

**AMBIENT OPERATING
TEMPERATURE - MIN** -20 °C

**AMBIENT OPERATING
TEMPERATURE - MAX** 55 °C

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the

Additional information

CURRENT LIMITING CLASS	3
FEATURES	Additional equipment possible
SUITABLE FOR	Flush-mounted installation

	temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Ressurser

DECLARATIONS OF CONFORMITY	eaton-mcb-declaration-of-conformity-eu250395en.pdf
INSTALLERINGSINSTRUKSJONER	eaton-rccb-rcbo-g9-il019140zu.pdf
MCAD MODEL	faz_3p.dwg faz_3p.stp

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATO: