

# Specifications



Photo is representative

## Eaton 189646

NZMH4-4-PX630/VAR. NZM4 PXR25 circuit breaker - integrated energy measurement class 1, 630A, 4p, variable, Screw terminal

### General specifications

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM molded case circuit breaker electronic |
| <b>CATALOG NUMBER</b>       | 189646                                                          |
| <b>MODEL CODE</b>           | NZMH4-4-PX630/VAR                                               |
| <b>EAN</b>                  | 4015081875931                                                   |
| <b>PRODUCT LENGTH/DEPTH</b> | 375 mm                                                          |
| <b>PRODUCT HEIGHT</b>       | 170 mm                                                          |
| <b>PRODUCT WIDTH</b>        | 280 mm                                                          |
| <b>PRODUCT WEIGHT</b>       | 25.5 kg                                                         |
| <b>COMPLIANCES</b>          | RoHS conform                                                    |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC                                             |
| <b>GLOBAL CATALOG</b>       | 189646                                                          |

## Product specifications

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>AMPERAGE RATING</b>                                                                  | 630 A                                                                                                                            |
| <b>VOLTAGE RATING</b>                                                                   | 690 V - 690 V                                                                                                                    |
| <b>CIRCUIT BREAKER FRAME TYPE</b>                                                       | NZM4                                                                                                                             |
| <b>FEATURES</b>                                                                         | Protection unit<br>Motor drive optional                                                                                          |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                                                                                       |

## Resources

|                                   |                                                                                                                                                  |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                  | <a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a><br><a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a> |
| <b>CATALOGS</b>                   | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>                                                                                   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250294en.pdf</a>                                                       |
| <b>DRAWINGS</b>                   | <a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-023.eps</a>                                                                                |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-circuit-breaker-basic-unit-bg4-il012101zu.pdf</a>                                                                              |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">Introduction of the new digital circuit breaker NZM</a><br><a href="#">The new digital NZM Range</a>                                 |
| <b>MCAD MODEL</b>                 | <a href="#">DA-CD-nzm4_4p</a><br><a href="#">DA-CS-nzm4_4p</a>                                                                                   |
| <b>PEP ECO-PASSPORT</b>           | <a href="#">eaton-molded-case-switches-pep-eato-00230-v0101-en.pdf</a>                                                                           |
| <b>TECHNICAL DATA SHEETS</b>      | <a href="#">eaton-nzm-technical-information-sheet</a>                                                                                            |

|                                                                 |                                                                                                      |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                                           |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                                               |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                                               |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                                               |
| <b>POLLUTION DEGREE</b>                                         | 3                                                                                                    |
| <b>MOUNTING METHOD</b>                                          | Built-in device fixed built-in technique<br>Fixed                                                    |
| <b>CLIMATIC PROOFING</b>                                        | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                       |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 49 W                                                                                                 |
| <b>UTILIZATION CATEGORY</b>                                     | B (IEC/EN 60947-2)                                                                                   |
| <b>ISOLATION</b>                                                | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts) |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 70 °C                                                                                                |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                      | -25 °C                                                                                               |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                        | 70 °C                                                                                                |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                        | 40 °C                                                                                                |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>      | 0                                                                                                    |

|                                                                |                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                       | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110                                                                                                                                                                                                                                                                                                                                              |
| <b>DEGREE OF PROTECTION</b>                                    | IP20<br>IP20 (basic degree of protection, in the operating controls area)                                                                                                                                                                                                                                                                                                                                    |
| <b>DIRECTION OF INCOMING SUPPLY</b>                            | As required                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>              | Screw connection                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>CURRENT RATING OF NEUTRAL CONDUCTOR</b>                     | 0 - 60% - 100% of phase conductor                                                                                                                                                                                                                                                                                                                                                                            |
| <b>LIFESPAN, MECHANICAL</b>                                    | 10000 operations                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>                   | IP66 (with door coupling rotary handle)<br>IP40 (with insulating surround)                                                                                                                                                                                                                                                                                                                                   |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>                     | IP10 (tunnel terminal)<br>IP00 (terminations, phase isolator and strip terminal)                                                                                                                                                                                                                                                                                                                             |
| <b>NUMBER OF POLES</b>                                         | Four-pole                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>                        | 10 segments of 80 mm x 1 mm (2x) at rear-side width extension<br>Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched)<br>10 segments of 50 mm x 1 mm (2x) at 1-hole module plate<br>Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal<br>Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal<br>Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched) |
| <b>LIFESPAN, ELECTRICAL</b>                                    | 3000 operations at 415 V AC-1<br>2000 operations at 690 V AC-1<br>3000 operations at 400 V                                                                                                                                                                                                                                                                                                                   |

|                  |                                                      |
|------------------|------------------------------------------------------|
|                  | AC-1                                                 |
| <b>FUNCTIONS</b> | Systems, cable, selectivity and generator protection |
| <b>TYPE</b>      | Circuit breaker                                      |

#### SPECIAL FEATURES

- LSI overload protection and delayed and non-delayed short-circuit protective device
- Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"
- USB interface for configuration and test function with Power Xpert Protection Manager software
- Interface module in equipment supplied.
- Optionally communication-capable with internal Modbus RTU module or CAM
- Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity  $I_{cn}$ )
- Rated current = rated uninterrupted current: 630 A

|                                                        |                                          |
|--------------------------------------------------------|------------------------------------------|
| <b>APPLICATION</b>                                     | Use in unearthed supply systems at 690 V |
| <b>SHOCK RESISTANCE</b>                                | 15 g (half-sinusoidal shock 11 ms)       |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b> | Front side                               |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED</b>         | 630 A                                    |

|                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>HEAT DISSIPATION (IN)</b>                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>RELEASE SYSTEM</b>                                   | Electronic release                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>SHORT-CIRCUIT TOTAL BREAKTIME</b>                    | < 25 ms ( $\leq$ 415 V); < 35 ms (> 415 V)                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>RATED SHORT-TIME WITHSTAND CURRENT (T = 0.3 S)</b>   | 19.2 kA                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>RATED SHORT-TIME WITHSTAND CURRENT (T = 1 S)</b>     | 19.2 kA                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>SHORT-CIRCUIT RELEASE DELAYED SETTING - MAX</b>      | 6300 A                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>SHORT-CIRCUIT RELEASE DELAYED SETTING - MIN</b>      | 504 A                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX</b>  | 11340 A                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN</b>  | 1260 A                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>TERMINAL CAPACITY (CONTROL CABLE)</b>                | 0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)<br>0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)                                                                                                                                                                                                                                                                                                                                                |
| <b>TERMINAL CAPACITY (COPPER BUSBAR)</b>                | Max. 50 mm x 10 mm (2x) direct at switch rear-side connection<br>Max. 80 mm x 10 mm (2x) at rear-side width extension<br>Min. 60 mm x 10 mm at rear-side width extension<br>50 mm x 10 mm (2x) at rear-side 2-hole module plate<br>Min. 25 mm x 5 mm at rear-side 1-hole module plate<br>Min. 25 mm x 5 mm direct at switch rear-side connection<br>M10 at rear-side screw connection<br>Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate |
| <b>TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)</b> | 95 mm <sup>2</sup> - 240 mm <sup>2</sup> (6x) at rear-side width extension<br>35 mm <sup>2</sup> - 185 mm <sup>2</sup> (4x) at rear-side 2-hole module plate<br>95 mm <sup>2</sup> - 300 mm <sup>2</sup> (2x) at rear-side 1-hole module plate<br>95 mm <sup>2</sup> - 185 mm <sup>2</sup> (2x) at rear-side 2-hole module plate                                                                                                                  |

|                                                                                        |                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                        | 120 mm <sup>2</sup> - 300 mm <sup>2</sup> (1x) at rear-side 1-hole module plate<br>50 mm <sup>2</sup> - 240 mm <sup>2</sup> (4x) at 4-hole tunnel terminal<br>300 mm <sup>2</sup> (4x) at rear-side width extension |
| <b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>                             | 120 mm <sup>2</sup> - 185 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>50 mm <sup>2</sup> - 185 mm <sup>2</sup> (4x) direct at switch rear-side connection                                         |
| <b>TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)</b>                           | 50 mm <sup>2</sup> - 240 mm <sup>2</sup> (4x) at 4-hole tunnel terminal                                                                                                                                             |
| <b>HANDLE TYPE</b>                                                                     | Rocker lever                                                                                                                                                                                                        |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>                                         | 10 A                                                                                                                                                                                                                |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MIN</b>                                         | 2 A                                                                                                                                                                                                                 |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>                                        | 22680 A                                                                                                                                                                                                             |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>                                        | 1260 A                                                                                                                                                                                                              |
| <b>NUMBER OF OPERATIONS PER HOUR - MAX</b>                                             | 60                                                                                                                                                                                                                  |
| <b>OVERLOAD CURRENT SETTING (IR) - MAX</b>                                             | 630 A                                                                                                                                                                                                               |
| <b>OVERLOAD CURRENT SETTING (IR) - MIN</b>                                             | 252 A                                                                                                                                                                                                               |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ</b>     | 63 kA                                                                                                                                                                                                               |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b> | 50 kA                                                                                                                                                                                                               |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ</b>     | 50 kA                                                                                                                                                                                                               |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 HZ</b>     | 37 kA                                                                                                                                                                                                               |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 690 V, 50/60 HZ</b>     | 37 kA                                                                                                                                                                                                               |

|                                                                                 |                                                        |
|---------------------------------------------------------------------------------|--------------------------------------------------------|
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 400/415 V, 50/60 HZ</b>   | 187 kA                                                 |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 440 V, 50/60 HZ</b>       | 187 kA                                                 |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 525 V, 50/60 HZ</b>       | 143 kA                                                 |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 690 V, 50/60 HZ</b>       | 100 kA                                                 |
| <b>STANDARD TERMINALS</b>                                                       | Screw terminal                                         |
| <b>OPTIONAL TERMINALS</b>                                                       | Connection on rear. Strip<br>terminal. Tunnel terminal |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 240 V, 50/60 HZ</b>       | 275 kA                                                 |
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT AUXILIARY<br/>CONTACTS</b> | 6000 V                                                 |
| <b>RATED IMPULSE<br/>WITHSTAND VOLTAGE<br/>(UIMP) AT MAIN<br/>CONTACTS</b>      | 8000 V                                                 |
| <b>RATED INSULATION<br/>VOLTAGE (UI)</b>                                        | 1000 V AC                                              |

|                        |
|------------------------|
| <b>PROJECT NAME:</b>   |
| <b>PROJECT NUMBER:</b> |
| <b>PREPARED BY:</b>    |
| <b>DATE:</b>           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

