

Specifications



Eaton 168486

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 320A, plug-in module, NZMN3-A320-SVE

General specifications

PRODUCT NAME	Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
CATALOG NUMBER	168486
MODEL CODE	NZMN3-A320-SVE
EAN	4015081649662
PRODUCT LENGTH/DEPTH	335 mm
PRODUCT HEIGHT	215.2 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	6.38 kg
COMPLIANCES	RoHS conform
GLOBAL CATALOG	168486



Powering Business Worldwide

Product specifications

AMPERAGE RATING	320 A
VOLTAGE RATING	690 V - 690 V
FEATURES	Motor drive optional Protection unit
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF	Does not apply, since the entire switchgear needs to

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250292en.pdf
ECAD MODEL	DA-CE-ETN.NZMN3-A320-SVE
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-plug-in-adapter-nzm2-il01219023z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	nzmh3_me220_sve.dwg nzmh3_me220_sve.stp
PEP ECO-PASSPORT	eaton-molded-case-switches-pep-eato-00231-v0101-en.pdf
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

ASSEMBLIES	be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
MOUNTING METHOD	Built-in device plug-in technique
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	78.64 W
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
DEGREE OF PROTECTION	IP20
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
NUMBER OF POLES	Three-pole
SPECIAL FEATURES	Rated current = rated uninterrupted current: 320

A

POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Front side
--	------------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	320 A
--	-------

SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX	3200 A
--	--------

SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN	1920 A
--	--------

HANDLE TYPE	Rocker lever
--------------------	--------------

SHORT DELAY CURRENT SETTING (ISD) - MAX	0 A
--	-----

SHORT DELAY CURRENT SETTING (ISD) - MIN	0 A
--	-----

INSTANTANEOUS CURRENT SETTING (II) - MAX	3200 A
---	--------

INSTANTANEOUS CURRENT SETTING (II) - MIN	1500 A
---	--------

OVERLOAD CURRENT SETTING (IR) - MAX	320 A
--	-------

OVERLOAD CURRENT SETTING (IR) - MIN	250 A
--	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ	50 kA
--	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 500 V DC	30 kA
---	-------

RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 750 V DC	30 kA
---	-------

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.