

Specifications



Photo is representative



Eaton EP-400045

Eaton DA1 Variable frequency drive, 400 V AC, 3-phase, 18 A, 7.5 kW, IP66/NEMA 4X, Radio interference suppression filter, OLED display, UV resistant

General specifications

PRODUCT NAME	Eaton DA1 Variable frequency drive
---------------------	------------------------------------

CATALOG NUMBER	EP-400045
-----------------------	-----------

MODEL CODE	DA1-34018FB-B66O
-------------------	------------------

EAN	4015082950279
------------	---------------

PRODUCT LENGTH/DEPTH	235 mm
-----------------------------	--------

PRODUCT HEIGHT	310 mm
-----------------------	--------

PRODUCT WIDTH	210.5 mm
----------------------	----------

PRODUCT WEIGHT	6.6 kg
-----------------------	--------

CE
Certified by UL for use in
Canada
CSA-C22.2 No. 14
CUL
EAC
IEC/EN 61800-3
IEC/EN61800-3
IEC/EN61800-5
RCM
RoHS, ISO 9001
Safety: EN 61800-5-1: 2003

CERTIFICATIONS

Specification for general
requirements: IEC/EN
61800-2
UkrSEPRO
UL
UL 508C
UL Category Control No.:
NMMS, NMMS7
UL File No.: E172143
UL report applies to both
US and Canada

CATALOG NOTES

The brake resistors are
assigned based on the
maximum rated power of
the variable frequency
drive. Additional brake

EATON

Powering Business Worldwide

resistors and designs (e.g. different duty cycles) are available upon request.

General

CABLE LENGTH	100 m, screened, maximum permissible, Motor feeder
	150 m, unscreened, maximum permissible, Motor feeder
	200 m, screened, with motor choke, maximum permissible, Motor feeder
	300 m, unscreened, with motor choke, maximum permissible, Motor feeder
	C2 ≤ 5 m, Radio interference level, maximum motor cable length
	C3 ≤ 25 m, Radio interference level, maximum motor cable length
COMMUNICATION INTERFACE	CANopen®, built in EtherCAT, optional Ethernet IP, optional Modbus RTU, built in Modbus-TCP, optional OP-Bus (RS485), built in PROFIBUS, optional PROFINET, optional BACnet/IP, optional
CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	IP66 NEMA 4X
ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
FITTED WITH:	PC connection Control unit Breaking resistance Additional PCB protection Brake chopper IGBT inverter Internal DC link OLED display Radio interference suppression filter
FRAME SIZE	FS3
FUNCTIONS	4-quadrant operation possible
MOUNTING POSITION	Vertical
PRODUCT CATEGORY	Variable frequency drives
PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Climatic environmental conditions

ALTITUDE	Max. 1000 m Above 1000 m with 1 % derating per 100 m Max. 4000 m
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
CLIMATIC PROOFING	< 95 average relative humidity (RH), no condensation, no corrosion

PROTOCOL	CAN EtherNet/IP MODBUS Other bus systems PROFIBUS PROFINET IO TCP/IP BACnet/IP
SAFETY FUNCTION/LEVEL	STO (Safe Torque Off, SIL3, PLe Cat 3)
SUITABLE FOR	Branch circuits, (UL/CSA)
RADIO INTERFERENCE CLASS	C1: for conducted emissions only Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments C2, C3: depending on the motor cable length, the connected load, and ambient conditions.

Main circuit

EFFICIENCY	97 % (η)
HEAT DISSIPATION AT CURRENT/SPEED	165 W at 100% current and 0% speed 205 W at 100% current and 50% speed 271 W at 100% current and 90% speed 138 W at 50% current and 0% speed 138 W at 50% current and 50% speed 172 W at 50% current and 90% speed 88 W at 25% current and 0% speed 112 W at 25% current and 50% speed
INPUT CURRENT I_{LN} AT 150% OVERLOAD	21.8 A
LEAKAGE CURRENT AT GROUND I_{PE} - MAX	1.55 mA
MAINS SWITCH-ON FREQUENCY	Maximum of one time every 30 seconds
MAINS VOLTAGE - MIN	342 V
MAINS VOLTAGE - MAX	528 V
OPERATING MODE	Optional: Vector control with feedback (CLV) Sensorless vector control (SLV) Speed control with slip compensation U/f control
OUTPUT FREQUENCY - MIN	0 Hz
OUTPUT FREQUENCY - MAX	500 Hz
OUTPUT VOLTAGE (U₂)	400 V AC, 3-phase 480 V AC, 3-phase
OVERLOAD CURRENT I_L AT 150% OVERLOAD	27 A
RATED CONTROL SUPPLY VOLTAGE	10 V DC (U _s , max. 10 mA)
RATED FREQUENCY - MIN	48 Hz
RATED FREQUENCY - MAX	62 Hz
RATED OPERATIONAL POWER AT 380/400 V, 50 HZ, 3-PHASE	7.5 kW
RATED OPERATIONAL VOLTAGE	400 V AC, 3-phase 480 V AC, 3-phase
RESOLUTION	0.1 Hz (Frequency)

Motor rating

ASSIGNED MOTOR CURRENT I_M AT 400 V, 50 HZ, 150% OVERLOAD	15.2 A
ASSIGNED MOTOR CURRENT I_M AT 440 - 480 V, 60 HZ, 150% OVERLOAD	14 A
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	10 HP

	resolution, setpoint value)
SHORT-CIRCUIT PROTECTION RATING	30 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
STARTING CURRENT - MAX	200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section
SUPPLY FREQUENCY	50/60 Hz
SWITCHING FREQUENCY	8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
VOLTAGE RATING - MAX	480 VAC

Apparent power

APPARENT POWER AT 400 V 12.47 kVA

APPARENT POWER AT 480 V 14.96 kVA

Control circuit

NUMBER OF INPUTS (ANALOG) 2

NUMBER OF INPUTS (DIGITAL) 5

NUMBER OF OUTPUTS (ANALOG) 2

NUMBER OF OUTPUTS (DIGITAL) 2

NUMBER OF RELAY OUTPUTS 2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

RATED CONTROL VOLTAGE (UC) 24 V DC (external, max. 100 mA)

Braking function

BRAKING RESISTANCE 50 Ω

BRAKING TORQUE Max. 30 % MN, Standard - Main circuit
Max. 100 % of rated operational current I_e , variable, DC - Main circuit
Max. 100 % of rated operational current I_e with external braking resistor - Main circuit

SWITCH-ON THRESHOLD FOR THE BRAKING TRANSISTOR 780 VDC

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID 300 W

HEAT DISSIPATION CAPACITY PDISS 0 W

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID 0 W

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF Meets the product standard's requirements.

ENCLOSURES	
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY**

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

3D MODELS

[eaton-EP-400027-3d-model.stp](#)

[eaton-EP-400027-drawing.dwg](#)

APPLICATION NOTES

[eaton-powerxl-da1-operating-pm-bldc-motors-ap040051-en-us.pdf](#)

[eaton-powerxl-da1-vector-control-induction-motors-ap040028-en-us.pdf](#)

[eaton-powerxl-da1-use-of-multiple-ramps-ap040031-en-us.pdf](#)

[eaton-powerxl-da1-motor-vf-curves-induction-motors-ap040018-en-us.pdf](#)

[eaton-powerxl-da1-dc1-db1-de1-rapidlink5-firmware-update-ap040214-en-us.pdf](#)

[eaton-powerxl-da1-dc1-de1-internal-motor-protection-ap040016-en-us.pdf](#)

[Start, Stopp und Betrieb](#)

[eaton-powerxl-da1-droop-function-ap040023-en-us.pdf](#)

[eaton-powerxl-da1-starting-stopping-operation-ap040030-en-us.pdf](#)

[eaton-powerxl-vfd-dual-rating-ap040114-en-us.pdf](#)

[eaton-powerxl-da1-derating-ap040039-en-us.pdf](#)

[eaton-powerxl-da1-hoist-applications-ap040032-en-us.pdf](#)

[Electromagnetic compatibility \(EMC\)](#)

[eaton-powerxl-dx-comstick-3-ap040190-en-us.pdf](#)

	eaton-powerxl-da1-i-o-configuration-ap040034-en-us.pdf eaton-powerxl-da1-dc1-de1-conformal-coating-ap040182-en-us.pdf eaton-powerxl-da1-set-point-setting-ap040040-en-us.pdf eaton-powerxl-da1-master-slave-operation-ap040026-en-us.pdf eaton-powerxl-da1-pointer-to-parameter-ap040133-en-us.pdf eaton-powerxl-da1-pid-controller-ap040025-en-us.pdf eaton-powerxl-da1-dc1-de1-system-bus-ap040022-en-us.pdf
BROCHURES	eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf
CATALOGUES	Product Range Catalog Drives Engineering
DECLARATIONS OF CONFORMITY	eaton-variable-frequency-drive-declaration-of-conformity-uk251134en.pdf eaton-variable-frequency-drive-declaration-of-conformity-eu250651en.pdf
INSTALLATION INSTRUCTIONS	eaton-da1-variable-frequency-drive-il040061zu.pdf
INSTALLATION VIDEOS	Video PowerXL DA1 PowerXL Variable Frequency Drives DC1 and DA1 - EN
MANUALS AND USER GUIDES	eaton-da1-variable-frequency-drive-mn040063-en-us.pdf
MULTIMEDIA	Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

[System solutions based on EtherCAT](#)

[eaton-powerxl-da1-ethercat-esi-for-omron-v311.zip](#)

[eaton-powerxl-pcsoftware-drivesconnect-v1501.zip](#)

[eaton-powerxl-dx-cbl-pc-1m5-usb-driver.zip](#)

[eaton-powerxl-da1-profinet-gsdml-v226.zip](#)

[eaton-powerxl-da1-swd-codesys-v3-library.zip](#)

[eaton-powerxl-da1-ethercat-esi-v310.zip](#)

[eaton-powerxl-da1-canopen-eds-v250.zip](#)

SOFTWARE, FIRMWARE,
AND APPLICATIONS

[eaton-powerxl-da1-canopen-codesys-v3-library.zip](#)

[eaton-powerxl-da1-firmware-release-note-mz040041en-us.pdf](#)

[eaton-powerxl-dx-comstick3-ble-drivers.zip](#)

[eaton-powerxl-da1-devicenet-eds-v100.zip](#)

[eaton-powerxl-da1-profibus-gsd-v216.zip](#)

[eaton-powerxl-da1-profinet-tia-v12-library.zip](#)

[eaton-powerxl-dx-cbl-pc-3m0-usb-driver.zip](#)

[eaton-powerxl-da1-ethernetip-eds-v150.zip](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.