

# Specifications



Photo is representative

## Eaton 168481

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 400A, plug-in module, NZMN3-VE400-SVE

### General specifications

|                                 |   |
|---------------------------------|---|
| <b>PRODUCT NAME</b>             | Eaton Moeller series NZM<br>molded case circuit<br>breaker electronic |
| <b>CATALOG NUMBER</b>           | 168481  |
| <b>MODEL CODE</b>               | NZMN3-VE400-SVE   |
| <b>EAN</b>                      | 4015081649624   |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 335 mm  |
| <b>PRODUCT HEIGHT</b>           | 215.2 mm  |
| <b>PRODUCT WIDTH</b>            | 140 mm  |
| <b>PRODUCT WEIGHT</b>           | 7.72 kg   |
| <b>COMPLIANCES</b>              | RoHS conform  |
| <b>GLOBAL CATALOG</b>           | 168481  |



Powering Business Worldwide

## Product specifications

|   |  |
|---|--|
| <b>AMPERAGE RATING</b>  | 400 A  |
| <b>VOLTAGE RATING</b>   | 690 V - 690 V  |
| <b>FEATURES</b>   | Motor drive optional<br>Protection unit  |
| <b>10.10 TEMPERATURE RISE</b>   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.   |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.7 INSCRIPTIONS</b>  | Meets the product standard's requirements.   |
| <b>10.3 DEGREE OF PROTECTION OF</b>   | Does not apply, since the entire switchgear needs to   |

## Resources

|                                   |  |
|-----------------------------------|--|
| <b>BROCHURES</b>                  | <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a><br><a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a> |
| <b>CATALOGS</b>                   | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a>   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250293en.pdf</a>   |
| <b>ECAD MODEL</b>                 | <a href="#">DA-CE-ETN.NZMN3-VE400-SVE</a>  |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-circuit-breaker-plug-in-adapter-nzm2-il01219023z.pdf</a>   |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">Introduction of the new digital circuit breaker NZM</a><br><a href="#">The new digital NZM Range</a>                                 |
| <b>MCAD MODEL</b>                 | <a href="#">nzmh3_me220_sve.dwg</a><br><a href="#">nzmh3_me220_sve.stp</a>   |
| <b>PEP ECO-PASSPORT</b>           | <a href="#">eaton-molded-case-switches-pep-eato-00219-v0101-en.pdf</a>   |
| <b>TECHNICAL DATA SHEETS</b>      | <a href="#">eaton-nzm-technical-information-sheet</a>  |

|  |  |
|--|--|
| <b>ASSEMBLIES</b>  | be evaluated.  |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                        | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>             | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                              | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>      | Is the panel builder's responsibility.                             |
| <b>MOUNTING METHOD</b>   | Built-in device plug-in technique                                  |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>                 | 48 W   |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>           | 0  |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>       | 0  |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>         | 0  |
| <b>DEGREE OF PROTECTION</b>  | IP20   |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>                    | Screw connection   |
| <b>NUMBER OF POLES</b>   | Three-pole   |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>               | Front side   |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 400 A  |
| <b>HANDLE TYPE</b>   | Rocker lever   |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>                       | 4000 A   |
| <b>SHORT DELAY CURRENT</b>   | 400 A  |

|  |        |
|--|--------|
| <b>SETTING (ISD) - MIN</b>   |        |
| <b>INSTANTANEOUS<br/>CURRENT SETTING (II) -<br/>MAX</b>  | 4400 A |
| <b>INSTANTANEOUS<br/>CURRENT SETTING (II) -<br/>MIN</b>  | 800 A  |
| <b>OVERLOAD CURRENT<br/>SETTING (IR) - MAX</b>   | 400 A  |
| <b>OVERLOAD CURRENT<br/>SETTING (IR) - MIN</b>   | 200 A  |
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT<br/>400/415 V, 50/60 HZ</b> | 50 kA  |

|                        |
|------------------------|
| <b>PROJECT NAME:</b>   |
| <b>PROJECT NUMBER:</b> |
| <b>PREPARED BY:</b>    |
| <b>DATE:</b>           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

