

Produktdatablad

Spesifikasjoner



Tidsrelé multifunksjon m/17,5 mm bred 1s-100t relé utgang 24-240V AC 8A 1CO

El-nummer:
4172527 RE17RMXMU

EAN: 3606480552786

Produktdata

Produktspekter	Harmony Timer Relays
Digitale utganger	Relé
Produkt eller type komponent	Modular timing relay
Bredde	17,5 mm
Kortnavn på utstyr	RE17R
Tidsforsinkelsestype	Pulse delay Safe-guard Bistable Interval
Tidsforsinkelsesområde	6...60 s 1...10 min 0.1...1 s 1...10 t 1...10 s 6...60 min 10...100 t
nominell utgangsstrøm	8 A

Teknisk data

kontakttype og sammensetning	1 C/O
Kontaktmateriale	Cadmium fri
Høyde	90 mm
Dybde	72 mm
start/stopp	Vribyter front panel
[Us] matespenning	24...240 V AC 50_60_HZ 24 V DC
spenningsområde	0.85...1.1 Us
nettfrekvens	50...60 Hz +/- 5 %
release of input voltage	10 V
tilkoblingsklemmer	Skruklemmer, 1 x 0.5...1 x 3.3 mm² (AWG 20...AWG 12) Solid uten endehylse Skruklemmer, 2 x 0.5...2 x 2.5 mm² (AWG 20...AWG 14) Solid uten endehylse Skruklemmer, 1 x 0.2...1 x 2.5 mm² (AWG 24...AWG 14) fleksibel med endehylse Skruklemmer, 2 x 0.2...2 x 1.5 mm² (AWG 24...AWG 16) fleksibel med endehylse
Tiltrekningsmoment	0,6...1 N.m i samsvar med IEC 60947-1
Kapslingsmateriale	Self-extinguishing
Nøyktighet	+/- 0.5 % i samsvar med IEC 61812-1
temperature drift	+/- 0.05 %/°C
spenningsdrift	+/- 0.2 %/V

Ansvarsfraskrivelse: Dokumentasjonen erstatter ikke opplysninger om produktene, og skal ikke brukes til å fastslå produktenes egnethet eller driftssikkerhet for bestemte bruksområder.

setting accuracy of time delay	+/- 10 % av full skala på 25 °C i samsvar med IEC 61812-1
Time delay type	Pulse delay - Ad- Pulse delayed relay w/ control signal Pulse delay - Ah- Pulse delayed relay (single cycle) w/ control signal Safe-guard - N- Safe-guard relay Safe-guard - O- Delayed Safe-guard relay Pulse delay - P- Pulse delayed relay w/ fixed pulse length Pulse delay - Pt- Pulse delayed relay w/ fixed pulse length and pause/summation Bistable - TI- Bistable relay w/ control signal on Bistable - Tt- Retriggerable bistable relay w/ control signal on Interval - W- Interval relay w/ control signal off
control signal pulse width	100 ms med last i parallell typisk 30 ms typisk
Isolasjonsmotstand	100 MOhm på 500 V DC i samsvar med IEC 60664-1
tilbakestillingstid	120 ms on de-energisation typisk
"on-load" -faktor	100 %
strømforbruk i VA	0...32 VA på 240 V AC
strømforbruk i W	0,6 W på 24 V DC
minimum brytestrøm	10 mA på 5 V DC
Maximum svitsjestrøm	8 A AC/DC
Maksimum brytespenning	250 V AC
bryteevne	2000 VA
operating frequency	10 Hz
elektrisk levetid	100000 sykluser for Ohmsk last (8 A på 250 V AC maksimum)
Mekanisk levetid	10000000 sykluser
dielektrisk styrke	2,5 kV 1 mA/1 minutt 50 Hz i samsvar med IEC 61812-1
[Uimp] Nominell impulsspenning	5 kV under 1.2/50 µs
power on delay	100 ms
Merking	CE
krypavstand	4 kV/3 i samsvar med IEC 60664-1
sikkerhet pålitelighet data	MTTFd = 296.8 år B10d = 270000
monteringsposisjon	Alle posisjoner i forhold til normalplanet loddrett feste
monteringssupport	35 mm DIN-skinne i samsvar med IEC 60715
lokal varslng	LED indikasjon for on steady: relay energised, no timing in progress LED indikasjon 80% PÅ og 20% OFF for flashing: timing in progress LED indikasjon 5% PÅ og 95% OFF for pulsing: relay de-energised, no timing in progress (except function Di-D, Li-L)
funksjonen tilgjengelig	Ad- Pulse delayed relay w/ control signal-1 C/O Ah- Pulse delayed relay (single cycle) w/ control signal-1 C/O N- Safe-guard relay-1 C/O O- Delayed Safe-guard relay-1 C/O P- Pulse delayed relay w/ fixed pulse length-1 C/O Pt- Pulse delayed relay w/ fixed pulse length and pause/summation-1 C/O TI- Bistable relay w/ control signal on-1 C/O Tt- Retriggerable bistable relay w/ control signal on-1 C/O W- Interval relay w/ control signal off-1 C/O
Vekt	0,07 kg
Kontrolltype	Uten testknappen
Number of functions	9
tidsforsinker type	Ad, Ah, N, O, P, Pt, TI, Tt, W
funksjonalitet	Multifunksjon

Kompatibilitetskode	RE17
---------------------	------

Miljø

Immunitet mot mikroavbrytelser	20 ms
Standarder	2006/95/EC 2004/108/EC IEC 61000-6-1 IEC 61000-6-4 IEC 61000-6-2 IEC 61000-6-3 IEC 61812-1
Produktsertifikater	cULus GL CSA
Omgivelsestemperatur for lagring	-30...60 °C
Omgivelsestemperatur drift	-20...60 °C
IP-grad	IP20 i samsvar med IEC 60529 (tilkoplingsblokk) IP40 i samsvar med IEC 60529 (kapsling) IP50 i samsvar med IEC 60529 (frontplate)
Vibrasjonsmotstand	20 m/s² (f= 10...150 Hz) conforming to IEC 60068-2-6
Støtmotstand	15 gn for 11 ms i samsvar med IEC 60068-2-27
relativ fuktighet	93 % uten kondens i samsvar med IEC 60068-2-30
Elektromagnetisk kompatibilitet	Immunitetstest for elektrostatisk utladning: test nivå: 6 kV (i kontakt) nivå 3 i samsvar med IEC 61000-4-2 Immunitetstest for elektrostatisk utladning: test nivå: 8 kV (i luft) nivå 3 i samsvar med IEC 61000-4-2 Mottakelig for elektromagnetiske felt: test nivå: 10 V/m (80 MHz to 1 GHz) nivå 3 i samsvar med IEC 61000-4-3 Electrical fast transient/burst immunity test: test nivå: 1 kV (kapasitiv koble klipp) nivå 3 i samsvar med IEC 61000-4-4 Electrical fast transient/burst immunity test: test nivå: 2 kV (direkte) nivå 3 i samsvar med IEC 61000-4-4 1.2/50 µs sjokkbølge immunisjonstest: test nivå: 1 kV (differensialmodus) nivå 3 i samsvar med IEC 61000-4-5 1.2/50 µs sjokkbølge immunisjonstest: test nivå: 2 kV (felles modul) nivå 3 i samsvar med IEC 61000-4-5 Gjennomført RF-forstyrrelser: test nivå: 10 V (0.15...80 MHz) nivå 3 i samsvar med IEC 61000-4-6 Spenningsfall og avbrudd immunitet test: test nivå: 0 % (en syklus) i samsvar med IEC 61000-4-11 Spenningsfall og avbrudd immunitet test: test nivå: 70 % (25/30 sykluser) i samsvar med IEC 61000-4-11 Strålt og ledet elektromagnetisme: klasse B i samsvar med EN 55022

Forpakkingsinformasjon

Enhetsstype pakke 1	PCE
Antall enheter i pakke 1	1
Pakke 1 Høyde	3,000 cm
Pakke 1 Bredde	8,300 cm
Pakke 1 Vekt	9,600 cm
Package 1 Weight	80,000 g
Enhetsstype pakke 2	S02
Antall enheter i pakke 2	40
Pakke 2 Høyde	15,000 cm
Pakke 2 Bredde	30,000 cm
Pakke 2 Lengde	40,000 cm

Pakke 2 Vekt	3,669 kg
--------------	----------

Logistikkinformasjon

Opprinnelsesland	ID
------------------	----

Garantiperiode

Garanti	18 måneder
---------	------------

Environmental Data

Schneider Electric tar sikte på å oppnå Net Zero-status innen 2050 gjennom partnerskap med leverandørkjeden, materialer med lavere slagkraft og sirkularitet via vår pågående "Use Better, Use Longer, Use Again"-kampanje for å forlenge produktlevetiden og resirkulerbarheten.

Environmental Data forklart >

Hvordan vi vurderer produktets bærekraft >

Miljøfotavtrykk	
Samlet klimagassutslipp gjennom livsløpet	55
PEP (Product Environmental Profile)	Produktmiljøprofil

Use Better


Materialer og emballasje	
Emballasje med resirkulert papp	Ja
Emballasje uten plast	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet)
SCIP-nummer	7bdc2711-0ad2-427c-8ece-532c5e9f09d7

Use Again

Ompakking og reproduksjon	
Produktets livssyklus	Informasjon om levetidsslutt
Tilbaketakning	No


Dimensions Drawings

Width 17.5 mm




Connections and Schema

Internal Wiring Diagram



Wiring Diagram



1) Contact Y1:

- Control for functions B, C, Ac, Bw, Ad, Ah, N, O, W, T, Tt.
- Partial stop for functions At, Ht and Pt.
- Function D if Di selected.
- Not used for functions A, H and P.


Technical Description

Function Ad : Pulse Delayed Relay with Control Signal

Description

After power-up, pulsing or maintaining of control contact C starts the timing T.
At the end of this timing period T, the output R closes.
The output R will be reset the next time control contact C is pulsed or maintained.

Function: 1 Output



Function Ah : Pulse Delayed Relay (Single Cycle) with Control Signal

Description

After power-up, pulsing or maintaining of control contact C starts the timing T. A single cycle then starts with 2 timing periods T of equal duration (start with output in rest position).
Output R closes at the end of the first timing period T and reverts to its initial position at the end of the second timing period T.
Control contact C must be reset in order to re-start the single flashing cycle.

Function: 1 Output



Function N : Retriggerable Interval Relay with Control Signal On

Description

After power-up and an initial control pulse C, the output R closes.
If the interval between two control pulses C is greater than the set timing period T, timing elapses normally and the output R closes at the end of the timing period. If the interval is not greater than the set timing period, the output R remains closed until this condition is met.

Function: 1 Output



Function O : Retriggerable Interval Delayed Relay with Control Signal On

Description

An initial timing period T begins on energisation. At the end of this timing period, the output R closes. As soon as there is a control pulse C, the output R reverts to its initial state until the interval between two control pulses is less than the value of the set timing period T. Otherwise, the output R closes at the end of the timing period T.

Function: 1 Output



Function P : Pulse Delayed Relay with Fixed Pulse Length

Description

The timing period T begins on energisation.
At the end of this period, the output R closes for a fixed time P.

Function: 1 Output




P = 500 ms

Function Pt : Pulse Delayed Relay (Summation and Fixed Pulse Length) with Control Signal Off

Description

On energisation, timing period T starts (it can be interrupted by operating the Gate control contact G).
At the end of this period, the output R closes for a fixed time P.

Function: 1 Output




$T = t1 + t2 + \dots$
 $P = 500 \text{ ms}$

Function TL : Bistable Relay with Control Signal On

Description

After power-up, pulsing or maintaining of control contact Y1 switches the output on.
A second pulse on the control contact Y1 switches the output relay off.



Function Tt : Retriggerable Bistable Relay with Control Signal On

Description

After power-up, pulsing or maintaining of control contact C switches output R on and starts timing T.
The output switches off at the end of the timing period T or following a second pulse on the control contact C.

Function: 1 Output



Function W : Interval Relay with Control Signal Off


Description

After power-up and opening of the control contact, the output(s) close(s) for a timing period T.
At the end of this timing period the output(s) revert(s) to its/their initial state.
The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.).


Legend

-  Relay de-energised
-  Relay energised
-  Output open
-  Output closed

C	Control contact
G	Gate
R	Relay or solid state output
R1/R2	2 timed outputs
R2 inst.	The second output is instantaneous if the right position is selected
T	Timing period
Ta -	Adjustable On-delay
Tr -	Adjustable Off-delay
U	Supply

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony Timer Relay



Flexible choice of screw or spring connection terminals for wiring.

One product reference covering 28 timing functions, 2 outputs, and a wide range of supply voltage 24...240 V AC/DC.

Dust and unintended human intervention avoided thanks to the IP50 lead-sealable settings protection cover.

A Dial-Pointer LED indicator that enhances ease of operation in difficult environments such as dusty or low-light conditions

Different mounting style to meet your preference:
DIN rail mount with product width: 17.5 mm/0.69 in. 22.5 mm/0.88 in.
Plug in mounting with socket

Offer Marketing Illustration

Product benefits / Features

Features

Harmony Timer Relay



"Diagnostic button" to check downstream circuit immediately, shorten the commission and troubleshooting time



Compatible with a wide range of applications including machines, buildings, water segments, and HVAC.



Wide range of time delay for adjustment: from 0.01 s to 999 hrs.



Compliant with IEC 60255-1 standard, and a wide array of product certifications such as UL, CE, CSA, EAC.




Unprecedented accuracy, predictive maintenance, and superior security.



Image of product / Alternate images

Alternative








Image of product in real life situation

