

Specifications



Photo is representative



Eaton 109669

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 320A, busbar terminal for CU N, frame 3, A320

General specifications

PRODUCT NAME	Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
CATALOG NUMBER	109669
MODEL CODE	NZMN3-A320
EAN	4015081092550
PRODUCT LENGTH/DEPTH	166 mm
PRODUCT HEIGHT	275 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	6.095 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC IEC/EN 60947
GLOBAL CATALOG	109669

Product specifications

AMPERAGE RATING	320 A
VOLTAGE RATING	690 V - 690 V
CIRCUIT BREAKER FRAME TYPE	NZM3
FEATURES	Motor drive optional Protection unit
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGS	eaton-digital-nzm-brochure-br013003en-en-us.pdf
CHARACTERISTIC CURVE	eaton-circuit-breaker-tripping-characteristic-nzm-mccb-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-circuit-breaker-nzm-mccb-characteristic-curve-031.eps
DRAWINGS	eaton-circuit-breaker-nzm-mccb-characteristic-curve-034.eps
ECAD MODEL	eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250292en.pdf
INSTALLATION INSTRUCTIONS	eaton-circuit-breaker-switch-nzm-mccb-dimensions-016.eps
INSTALLATION VIDEOS	eaton-circuit-breaker-nzm-mccb-dimensions-020.eps
MCAD MODEL	ETN.109669.edz
PEP ECO-PASSPORT	eaton-circuit-breaker-basic-device-nzmn-b-i01208009z.pdf
TECHNICAL DATA SHEETS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
	DA-CD-nzm3_3p
	DA-CS-nzm3_3p
	eaton-molded-case-switches-pep-eato-00184-v0101-en.pdf
	eaton-nzm-technical-information-sheet

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
POLLUTION DEGREE	3
MOUNTING METHOD	Fixed Built-in device fixed built-in technique
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	78.64 W
UTILIZATION CATEGORY	A (IEC/EN 60947-2)
ISOLATION	300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
PROTECTION AGAINST DIRECT CONTACT	Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
DEGREE OF PROTECTION	IP20 IP20 (basic degree of protection, in the operating controls area)
DIRECTION OF INCOMING SUPPLY	As required
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
LIFESPAN, MECHANICAL	15000 operations
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION (IP), FRONT SIDE	IP66 (with door coupling rotary handle) IP40 (with insulating surround)
DEGREE OF PROTECTION (TERMINATIONS)	IP00 (terminations, phase isolator and strip terminal) IP10 (tunnel terminal)
NUMBER OF POLES	Three-pole
TERMINAL CAPACITY (COPPER STRIP)	Max. 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm Min. 6 segments of 16 mm x 0.8 mm at box terminal 10 segments of 50 mm x 1 mm (2x) at rear-side width extension Max. 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm at rear-side connection (punched)
	Max. 8 segments of 24 mm x 1 mm (2x) at box terminal Min. 6 segments of 16 mm x 0.8 mm at rear-side connection (punched)
LIFESPAN, ELECTRICAL	2000 operations at 690 V AC-3 2000 operations at 500 V DC-3 3000 operations at 690 V AC-1

	5000 operations at 750 V DC-1 5000 operations at 415 V AC-1 2000 operations at 415 V AC-3 5000 operations at 400 V AC-1 5000 operations at 500 V DC-1 2000 operations at 750 V DC-3 2000 operations at 400 V AC-3
FUNCTIONS	System and cable protection
TYPE	Circuit breaker
SPECIAL FEATURES	<ul style="list-style-type: none"> • Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn) • Rated current = rated uninterrupted current: 320 A • Terminal capacity hint: Up to 240 mm² can be connected depending on the cable manufacturer.
APPLICATION	Use in unearthing supply systems at 690 V
SHOCK RESISTANCE	20 g (half-sinusoidal shock 20 ms)
POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT	Front side
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	320 A
RELEASE SYSTEM	Thermomagnetic release
SHORT-CIRCUIT TOTAL BREAKTIME	< 10 ms
RATED SHORT-TIME	3.3 kA

**WITHSTAND CURRENT (T
= 0.3 S)**

**RATED SHORT-TIME
WITHSTAND CURRENT (T
= 1 S)** 3.3 kA

SHORT-CIRCUIT RELEASE

**NON-DELAYED SETTING -
MAX** 3200 A

SHORT-CIRCUIT RELEASE

**NON-DELAYED SETTING -
MIN** 1920 A

**TERMINAL CAPACITY
(CONTROL CABLE)** 0.75 mm² - 2.5 mm² (1x)
0.75 mm² - 1.5 mm² (2x)

**TERMINAL CAPACITY
(COPPER BUSBAR)** Max. 30 mm x 10 mm + 30
mm x 5 mm direct at
switch rear-side
connection
Max. 10 mm x 50 mm (2x)
at rear-side width
extension
Min. 20 mm x 5 mm direct
at switch rear-side
connection
M10 at rear-side screw
connection

**TERMINAL CAPACITY
(COPPER SOLID
CONDUCTOR/CABLE)** 16 mm² (2x) at box
terminal
16 mm² (1x) at tunnel
terminal
16 mm² (2x) direct at
switch rear-side
connection
16 mm² (1x) direct at
switch rear-side
connection
300 mm² (2x) at rear-side
width extension

**TERMINAL CAPACITY
(ALUMINUM SOLID
CONDUCTOR/CABLE)** 16 mm² (1x) at tunnel
terminal

**TERMINAL CAPACITY
(COPPER STRANDED
CONDUCTOR/CABLE)** 25 mm² - 120 mm² (2x) at
box terminal
25 mm² - 240 mm² (2x)
direct at switch rear-side
connection
16 mm² - 185 mm² (1x) at
1-hole tunnel terminal
25 mm² - 240 mm² (1x)
direct at switch rear-side
connection
35 mm² - 240 mm² (1x) at
box terminal

**TERMINAL CAPACITY
(ALUMINUM STRANDED
CONDUCTOR/CABLE)** 25 mm² - 185 mm² (1x) at
tunnel terminal
50 mm² - 240 mm² (1x) at
2-hole tunnel terminal

	50 mm ² - 240 mm ² (2x) at 2-hole tunnel terminal
HANDLE TYPE	Rocker lever
SHORT DELAY CURRENT SETTING (ISD) - MAX	0 A
SHORT DELAY CURRENT SETTING (ISD) - MIN	0 A
INSTANTANEOUS CURRENT SETTING (II) - MAX	3200 A
INSTANTANEOUS CURRENT SETTING (II) - MIN	1920 A
NUMBER OF OPERATIONS PER HOUR - MAX	60
OVERLOAD CURRENT SETTING (IR) - MAX	320 A
OVERLOAD CURRENT SETTING (IR) - MIN	250 A
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 Hz	85 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 Hz	50 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 Hz	35 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 500 V DC	30 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 Hz	13 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 690 V, 50/60 Hz	5 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 750 V DC	30 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 400/415 V, 50/60 Hz	105 kA
RATED SHORT-CIRCUIT MAKING CAPACITY ICM	74 kA

AT 440 V, 50/60 Hz**RATED SHORT-CIRCUIT****MAKING CAPACITY ICM**

53 kA

AT 525 V, 50/60 Hz**RATED SHORT-CIRCUIT****MAKING CAPACITY ICM**

40 kA

AT 690 V, 50/60 Hz**STANDARD TERMINALS**

Screw terminal

OPTIONAL TERMINALSBox terminal. Connection
on rear. Tunnel terminal**RATED SHORT-CIRCUIT****MAKING CAPACITY ICM**

187 kA

AT 240 V, 50/60 Hz**RATED IMPULSE****WITHSTAND VOLTAGE
(UIMP) AT AUXILIARY
CONTACTS**

6000 V

RATED IMPULSE**WITHSTAND VOLTAGE
(UIMP) AT MAIN
CONTACTS**

8000 V

VOLTAGE RATING (DC)

750 VDC

RATED INSULATION**VOLTAGE (UI)**

1000 V AC

PROJECT NAME:**PROJECT NUMBER:****PREPARED BY:****DATE:****Eaton Corporation plc**

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the
latest product and support
information.