

Specifications



Eaton 168527

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3-pole, 630A, plug-in module

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Moeller series NZM molded case circuit breaker electronic |
| CATALOG NUMBER | 168527 |
| MODEL CODE | NZMS3-VE630-SVE |
| EAN | 4015081650040 |
| PRODUCT LENGTH/DEPTH | 335 mm |
| PRODUCT HEIGHT | 215.2 mm |
| PRODUCT WIDTH | 140 mm |
| PRODUCT WEIGHT | 7.72 kg |
| COMPLIANCES | RoHS conform |
| GLOBAL CATALOG | 168527 |



Powering Business Worldwide

Product specifications

| | |
|---|--|
| AMPERAGE RATING | 630 A |
| VOLTAGE RATING | 690 V - 690 V |
| FEATURES | Motor drive optional Protection unit |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF | Does not apply, since the entire switchgear needs to |

Resources

| | |
|-----------------------------------|--|
| BROCHURES | eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf |
| CATALOGS | eaton-digital-nzm-catalog-ca013003en-en-us.pdf |
| DECLARATIONS OF CONFORMITY | eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250293en.pdf |
| ECAD MODEL | DA-CE-ETN.NZMS3-VE630-SVE |
| INSTALLATION INSTRUCTIONS | eaton-circuit-breaker-plug-in-adapter-nzm2-il01219023z.pdf |
| INSTALLATION VIDEOS | The new digital NZM Range Introduction of the new digital circuit breaker NZM |
| MCAD MODEL | nzmh3_me220_sve.stp nzmh3_me220_sve.dwg |
| PEP ECO-PASSPORT | eaton-molded-case-switches-pep-eato-00219-v0101-en.pdf |
| TECHNICAL DATA SHEETS | eaton-nzm-technical-information-sheet |

| | |
|---|--|
| ASSEMBLIES | be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| MOUNTING METHOD | Built-in device plug-in technique |
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT | 119.07 W |
| NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS) | 0 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 0 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 0 |
| DEGREE OF PROTECTION | IP20 |
| ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT | Screw connection |
| NUMBER OF POLES | Three-pole |
| POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT | Back side |
| HANDLE TYPE | Rocker lever |
| SHORT DELAY CURRENT SETTING (ISD) - MAX | 6300 A |
| SHORT DELAY CURRENT SETTING (ISD) - MIN | 630 A |
| INSTANTANEOUS CURRENT SETTING (II) - | 7560 A |

| | |
|--|--------|
| MAX | |
| INSTANTANEOUS CURRENT SETTING (II) - MIN | 1260 A |
| OVERLOAD CURRENT SETTING (IR) - MAX | 630 A |
| OVERLOAD CURRENT SETTING (IR) - MIN | 315 A |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ | 100 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ | 70 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ | 65 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 525 V, 50/60 HZ | 18 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 690 V, 50/60 HZ | 6 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 525 V, 50/60 HZ | 36 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 400/415 V, 50/60 HZ | 70 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 230 V, 50/60 HZ | 100 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 690 V, 50/60 HZ | 25 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (IEC/EN 60947) AT 440 V, 50/60 HZ | 65 kA |
| RATED SHORT-CIRCUIT BREAKING CAPACITY ICU (UL489, CSA22.2) AT 240 V, 60 HZ | 100 kA |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.