



Nexans Ref.: 10590281
Country Ref.: 1050712
EAN 13: 7045210138511

FIRE PERFORMANCE CLASS



E_{ca}

Installation cable

STANDARDS

Test IEC 60332-1-2

National NEK 535

Installation cable for surface mount/visible installations. Can be used indoor and outdoor, but not suitable for being buried in the ground.

Minimum bending diameter, one-time 90 degree bend: 2xD

Minimum bending diameter, sharper bends: 4xD

(D = Outer diameter of cable)



Conductor flexibility
Solid class 1



Lead free
Yes



Rated Voltage U_o/U (U_m)
300/500 V



Max.conductor temp.in service
70 °C



RoHS compliant
Yes

CHARACTERISTICS

Construction characteristics

Conductor flexibility	Solid class 1
Conductor material	Annealed copper
Conductor shape	Round, massive
Insulation	PVC
Lead free	Yes
Material of filler / inner sheath	PE
Outer sheath	PVC
Screen	Longitudinal aluminium tape + copper wire
Sheath colour	White
With Green/Yellow core	No

Dimensional characteristics

Approximate weight	13.4 kg/100m
Approximate weight	134 kg/km
Conductor cross-section	1.5 mm ²
Conductor diameter	1.4 mm
Height	- mm
Nominal outer diameter	8.7 mm
Number of cores	3
Width	- m

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	300/500 V
---	-----------

Usage characteristics

Ambient installation temperature	10 °C
Field of application	-
Max. conductor temperature in service	70 °C
Packaging	Box
RoHS compliant	Yes