



## 12V 12Ah 20HR Valve Regulated Lead Acid Battery, Non-Spillable, Faston 6.35, HB

### Basic data:

|      |               |
|------|---------------|
| ID   | 0118780014    |
| GTIN | 7630268415181 |



### Features:

CP12-12 BNP, 3.6Kg, 151x98x99(L\*W\*H) mm, Non-Flame-Retardant Shell

### Technical data:

|                                                  |                      |
|--------------------------------------------------|----------------------|
| Model:                                           | Lead (dry cell, AGM) |
| Type:                                            | Stationary           |
| Application:                                     | Cyclic               |
| Suitable for various applications:               | Yes                  |
| Suitable for UPS:                                | Yes                  |
| Suitable for battery charger unit:               | Yes                  |
| Suitable for telecom:                            | Yes                  |
| Nominal voltage:                                 | 12 V                 |
| Capacity 15h:                                    | 11 Ah                |
| Capacity 20h:                                    | 12 Ah                |
| Connector:                                       | Faston 6.35          |
| Length:                                          | 151 mm               |
| Width:                                           | 98 mm                |
| Height including pole:                           | 99 mm                |
| Weight:                                          | 3.6 kg               |
| Ambient temperature:                             | -20 ... 60 °C        |
| Fire resistance according to UL94:               | HB                   |
| Lifespan at 20 °C:                               | 5 year               |
| Number of cycles to a depth of discharge of 100% | 300                  |
| Number of cycles to a depth of discharge of 80%  | 400                  |
| Number of cycles to a depth of discharge of 60%  | 500                  |
| Number of cycles to a depth of discharge of 50%  | 600                  |