



# 12V 7Ah 20HR Valve Regulated Lead Acid Battery, Non-Spillable, Faston 4.8, V0

## Basic data:

|      |               |
|------|---------------|
| ID   | 0118780007    |
| GTIN | 7630268415136 |



## Features:

CP12-7 EP, 1.9Kg, 151x65x99(L\*W\*H) mm, Flame Retardant Shell

## Technical data:

|                                                  |                      |
|--------------------------------------------------|----------------------|
| Model:                                           | Lead (dry cell, AGM) |
| Type:                                            | Stationary           |
| Application:                                     | Cyclic               |
| Suitable for various applications:               | Yes                  |
| Suitable for UPS:                                | Yes                  |
| Suitable for battery charger unit:               | Yes                  |
| Nominal voltage:                                 | 12 V                 |
| Capacity 15h:                                    | 6.5 Ah               |
| Capacity 20h:                                    | 7 Ah                 |
| Connector:                                       | Faston 4.8           |
| Length:                                          | 151 mm               |
| Width:                                           | 65 mm                |
| Height including pole:                           | 99 mm                |
| Weight:                                          | 1.9 kg               |
| Ambient temperature:                             | -20 ... 60 °C        |
| Fire resistance according to UL94:               | V0                   |
| Lifespan at 20 °C:                               | 5 year               |
| Number of cycles to a depth of discharge of 100% | 300                  |
| Number of cycles to a depth of discharge of 80%  | 400                  |
| Number of cycles to a depth of discharge of 60%  | 500                  |
| Number of cycles to a depth of discharge of 50%  | 600                  |