







System effekt (W): 26W
 Spenning: 220-240V
 Frekvens (Hz): 50/60Hz
 Maks. armaturer per sikring: B10: 32, B16: 50, C10: 52, C16: 85

Type lyskilde:	LED
Effektiv lysstrøm (lm):	3690lm
Lysutbytte:	142 lm/W
Farge temperatur:	3000K
Fargegjengivelse (Ra/CRI):	Ra>90
MacAdams faktor:	SDCM: 3
Levetid:	L90/B10>100.000
Lysstråling:	Direkte
Lysspredning:	60°
UGR:	UGR<25
Synlig flimmer (PstLM):	0.02
Stroboskopisk flimmer (SVM):	0

Styring: Ikke dimbar
Driver: 750mA

Isolasjonsklasse: Klasse II SELV
IP Klasse: IP20

Inneholder lyskilde med energiklasse: C
Breeam: Oppfyller Hea 01 krav til flimmerfri belysning (In-
Use: Hea 05)

Materiale:	Aluminium
Avskjermingens materiale:	Akryl (PMMA)

Montering: Utenpåliggende, Innendørs
Tilkobling: ShopLine skinne (adapter inkludert)

Lengde (mm) L:	583
Bredde (mm) W:	69
Høyde (mm) H:	69
Vekt (kg) brutto/netto:	1.14 / 0.91

Forpakningsstørrelse (mm): 600 x 85 x 120

