CONDUIT ID RANGE	APPLICABLE 5" [125mm] CONDUIT							
4.35" - 5.64" [110.49 mm - 143.50mm]	PVC SCH 40 PVC SCH 80 PVC DB 100 PVC DB 120 PVC DB 60 PVC EB 20 TC PVC EB 35 HDPE SCH 40 F2160 HDPE SCH 40 UL651A HDPE SCH 80 F2160 HDPE SCH 80 F2160 HDPE SCH 80 F2160 HDPE SCH 80 IL651A HDPE SDR 11			POLY PLUG CAL AM MFG			The state of the s	1
Applicable conduit types based on prod exceeding conduit ID dimensions specifi				Ø 5 / 4:				
standards: UL651, UL651A, ASTM F2160, NEMA TC 6 & 8					_			
		-	_					
SCH40		<u> </u>	-	Ø 4.30in [109.40mr		Ø 0.5		
SCH80		4.84in [123.01mm]				3.72in [94.61mm]		
SDR11		•		∅5.88in [149.35mn	_			oly Plug Margary Plugs
NOTES:	TITLE	POLY PLUG 5" 125mm						
1 Material: LDPE, Bla	Ck DDODDIETADY	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CAL AM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CAL AM MANUFACTURING IS PROHIBITED.		JC.MORENO	DATE: 05/03/2023 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CAL AM	
/ / Material LDI E, Dia	THE INFORMA			2250-050 MKT				NUFACTURING
	CAL AM MANU REPRODUCTIO			A	TOLERANCE	X.X±0.05 X.XXX±0.020		www.calam.net
				1:2	PRODUCT NUMBER:	2250-050	SHEET	1 OF 1
	ļ.		•		•			