


## Teknisk datablad

Artikkelnummer:  
111-04890

T50R



|                                       |                                                                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Produkt gruppe                        | Buntebånd for utvendig bruk                                                                                                     |
| Produkt familie                       | T-serie                                                                                                                         |
| Materiale                             | Polyamid 6.6 slagfast, scan black (PA66HIR(S))                                                                                  |
| Farge                                 | Sort (BK)                                                                                                                       |
| Antall pr.                            | pose                                                                                                                            |
| Bredde (W)                            | 4,6 mm                                                                                                                          |
| Brennbarhetsklasse                    | UL94 HB                                                                                                                         |
| Bunte Ø maks                          | 50,0 mm                                                                                                                         |
| Bunte Ø min.                          | 1,5 mm                                                                                                                          |
| Driftstemperatur - °C                 | -40 °C til +80 °C                                                                                                               |
| Halogenfri                            | Ja                                                                                                                              |
| Lengde (L)                            | 200 mm                                                                                                                          |
| Min. strekkfasthet                    | 225 N                                                                                                                           |
| Mont. verktøy                         | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP, EVO9iHT |
| Pakn.                                 | 100 stk.                                                                                                                        |
| Pakning 0 - Vekt netto                | 0,0013 kg                                                                                                                       |
| Rille                                 | Innvendige riller                                                                                                               |
| Spesifikasjoner / Normer              | IEC 60092 series                                                                                                                |
| Tykkelse (T)                          | 1,2 mm                                                                                                                          |
| UV-bestendig iht. ASTM D6779 (Ja/Nei) | Ja                                                                                                                              |
| Variant                               | Innvendige riller                                                                                                               |
| Åpningsbar lås (Ja/Nei)               | Nei                                                                                                                             |

