

Datasheet



ENSTO CLAMPO PRO ENSTO

Terminal block Y/G, Al/Cu 16-95 mm²
REF. KE62.3 | 1933067 | EAN. 6418677191879

1-pole, yellow/green, Al/Cu 16-95 mm²
[> Visit e-catalogue](#)

Main description:

1-pole, yellow/green, Al/Cu 16-95 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	50 - 70 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	16 - 70 mm ²
Connectable conductor cross section multi-wired (Min-Max)	16 - 95 mm ²
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	2
Mounting method	DIN rail (top hat rail) 35 mm

Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	24 mm
Height	49 mm
Depth	86 mm
Explosion-tested version 'Ex e'	No
Colour	Green/yellow
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

3D_KE62_PK2_V1.stp | IFC (5.45Mo)

2D_KE62_2.dxf | DXF (0.68Mo)



DD_KE62.pdf | PDF (0.12Mo)



2D_KE62.dwg | DWG (0.22Mo)

Agreements & certificates



CE_KE62_2024_EN.pdf | PDF (0.05Mo)



LGRP-01857-V01.01-EN.pdf | PDF (0.8Mo)



CE_KE62_2024_FI.pdf | PDF (0.05Mo)