

Datasheet



ENSTO CLAMPO PRO ENSTO

Terminal block Y/G, Al/Cu 35-150 mm²

REF. KE63.3 | 1933070 | EAN. 6418677191909

1-pole, yellow/green, Al/Cu 35-150 mm²

> [Visit e-catalogue](#)

Main description:

1-pole, yellow/green, Al/Cu 35-150 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	95 - 120 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	35 - 120 mm ²
Connectable conductor cross section multi-wired (Min-Max)	35 - 150 mm ²
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	2
Mounting method	DIN rail (top hat rail) 35 mm

Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	30 mm
Height	59 mm
Depth	95 mm
Explosion-tested version 'Ex e'	No
Colour	Green/yellow
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

2D_KE63_2.dxf | DXF (0.7Mo)

3D_KE63_PK2_V1.stp | IFC (5.6Mo)

 2D_KE63.dwg | DWG (0.22Mo)

 DD_KE63.pdf | PDF (0.13Mo)

Agreements & certificates

 CE_KE63_2024_EN.pdf | PDF (0.05Mo)

 LGRP-01858-V01.01-EN.pdf | PDF (0.8Mo)

 CE_KE63_2024_FI.pdf | PDF (0.05Mo)