

Datasheet



ENSTO CLAMPO PRO ENSTO

Terminal block Y/G, Al/Cu 35-240 mm²

REF. KE64.3 | 1933073 | EAN. 6418677191930

[> Visit e-catalogue](#)

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	15 - 185 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	35 - 185 mm ²
Connectable conductor cross section multi-wired (Min-Max)	35 - 240 mm ²
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	2
Mounting method	Direct mounting

Material insulation body	Thermoplastic
Operating temperature (Min-Max)	-5 - 80 °C
Width	37.5 mm
Height	67 mm
Depth	130 mm
Explosion-tested version 'Ex e'	No
Colour	Green/yellow
Inflammability class of insulation material according to UL 94	V2

Documentation

Technical documentation

IG_Clampo Pro.pdf | PDF (0.51Mo)

CAD & Design specs / BIM

DD_KE64.pdf | PDF (0.16Mo)

2D_KE64.dwg | DWG (0.24Mo)

2D_KE64_2.dxf | DXF (0.81Mo)

3D_KE64_PK2_V1.stp | IFC (4.51Mo)

Agreements & certificates

-  CE_KE64_2024_FI.pdf | PDF (0.05Mo)
-  CE_KE64_2024_EN.pdf | PDF (0.05Mo)
-  LGRP-01862-V01.01-EN.pdf | PDF (0.8Mo)