

Datasheet



ENSTO CLAMPO PRO ENSTO

Tapping connector Blue , Al/Cu 16-95 mm²

REF. KE67.2 | 1933078 | EAN. 6418677191985

Tapping block, blue , Al/Cu 16-95 mm²

> [Visit e-catalogue](#)

Main description:

Tapping block, blue , Al/Cu 16-95 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 - 240 mm².

Technical characteristics

| | |
|--|-------------------------------|
| Connectable conductor cross section fine-strand without cable end sleeve (Min-Max) | 50 - 70 mm ² |
| Connectable conductor cross section fine-strand with cable end sleeve (Min-Max) | 16 - 70 mm ² |
| Connectable conductor cross section multi-wired (Min-Max) | 16 - 95 mm ² |
| Rated current I _n | 220 A |
| Rated voltage | 800 V |
| Type of electrical connection 1 | Screw connection |
| Type of electrical connection 2 | Screw connection |
| Number of levels | 1 |
| Number of clamp positions per level | 4 |
| Suitable for conductor material | Aluminium/copper |
| Mounting method | DIN rail (top hat rail) 35 mm |

| | |
|--|---------------|
| Material insulation body | Thermoplastic |
| Operating temperature (Min-Max) | -5 - 80 °C |
| Width | 42 mm |
| Height | 49 mm |
| Depth | 86 mm |
| Explosion-tested version 'Ex e' | No |
| Closing plate required | No |
| Colour | Blue |
| Internally connected stages | No |
| Inflammability class of insulation material according to UL 94 | V2 |
| Halogen free | Yes |

Documentation

Technical documentation

 IG_Clampo Pro.pdf | PDF (0.51Mo)

Agreements & certificates

 CE_KE67_2024_FI.pdf | PDF (0.05Mo)

 CE_KE67_2024_EN.pdf | PDF (0.05Mo)

 LGRP-02004-V01.01-EN.pdf | PDF (0.78Mo)

CAD & Design specs / BIM

 2D_KE267_2.dxf | DXF (1.05Mo)

 3D_KE67_PK2_V1.stp | IFC (7.01Mo)

 2D_KE267.dwg | DWG (0.29Mo)

 DD_KE267.pdf | PDF (0.2Mo)