

Datasheet



ENSTO CLAMPO PRO ENSTO

Tapping connector Y/G, Al/Cu 35-150 mm²

REF. KE68.3 | 1933082 | EAN. 6418677192029

Tapping block, yellow/green, Al/Cu 35-150 mm²

> [Visit e-catalogue](#)

Main description:

Tapping block, yellow/green, Al/Cu 35-150 mm²

Description

Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm².

Technical characteristics

Connectable conductor cross section fine-strand without cable end sleeve (Min-Max)	95 - 120 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (Min-Max)	35 - 120 mm ²
Connectable conductor cross section multi-wired (Min-Max)	35 - 150 mm ²
Rated voltage	800 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Screw connection
Number of levels	1
Number of clamp positions per level	4
Suitable for conductor material	Aluminium/copper
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic

Operating temperature (Min-Max)	-5 - 80 °C
Width	51.5 mm
Height	59 mm
Depth	95 mm
Explosion-tested version 'Ex e'	No
Closing plate required	No
Colour	Green/yellow
Internally connected stages	No
Inflammability class of insulation material according to UL 94	V2
Halogen free	Yes

Documentation

Technical documentation

 IG_Clampo Pro.pdf | PDF (0.51Mo)

Agreements & certificates

 CE_KE68_2024_FI.pdf | PDF (0.05Mo)

 CE_KE68_2024_EN.pdf | PDF (0.05Mo)

 LGRP-02010-V01.01-EN.pdf | PDF (0.79Mo)

CAD & Design specs / BIM

 2D_KE268_2.dxf | DXF (1.04Mo)

 2D_KE268.dwg | DWG (0.29Mo)

 DD_KE268.pdf | PDF (0.21Mo)

 3D_KE68_PK2_V1.stp | IFC (6.69Mo)